## Eagle 300 Specs

The Toughest Jetters Available for Commercial Drain Cleaning Quality Built, Reliable Equipment... Expert Advice and Service

## Eagle 300 Trailer Jetter

Features and Specifications

18 GPM/4000 PSI Or 23 GPM/3000 PSI

Dual 31 Horsepower Kawasaki Engines, Liquid Cooled

Udor Super Duty Pumps And Gearbox Drives

300 Gallon Water Tank Capacity

36 Inch Wide Storage Compartment

500 Ft. Jetting Hose

1/2 Inch Included With 18/4000 Model

5/8 Inch Included With 24/3000 Model

100 Ft. 3/4 Inch Heavy Duty Supply Hose

2 Inch Air Gap Fill Pipe

Convenient Controls

Fuel Injected Kawasaki Engines

Multi-Port Digital Fuel Injection

Choke Free Starting

Liquid Cooled

Overhead Valve V-Twin

Pressurized Lubrication With Spin On Oil Filter

Cast Iron Cylinder Liners

824 Cc's

31 Hp @ 3600 RPM (SAE 1995 Rated)

47.1 Ft/Lbs Torque @ 3200 RPM

3 Year Warranty Through Kawasaki Engines

Rear Mounted Operator Controls

All Jetting controls are conveniently mounted at the rear of the Jetter for efficient and safe operation. Rear Controls Include:

Dual Engine Key Start And Stop

Synchronized Engine Throttle

Hose Reel Wind/Unwind

Water Pressure Adjustment

Water Flow Control, Pressure/Tank Return

Variable Pulse Control

Cold Weather Recirculation Port

Jetting Hose

Ultra Low Friction "Tough Skin" Cover

High Visibility Green Color

Bonded Construction Provides Maximum Kink Resistance

Excellent Cut, Gouge, And Abrasion Resistance

4000 PSI Working Pressure (16K Burst)

Kevlar Braid Reinforcement (1/2 Inch Size Only)

Available Options

Rotating Amber Beacon Light

10 Gallon Antifreeze Winterization Kit

. . .

600 Gallon Tandem Axle 10,000 GVW

Subaru Or Honda Engine Options

Extra Hose Length

Pintle Eye Hitch

Warthog Nozzles

Tyger Tail Hose Guide

Portable Reel Carts For Remote Jetting

Foot Pedal Controls

Heavy Duty Trailer

Heavy Duty 5" X 2" Tubular Steel Frame

Recessed LED Lighting

A-Frame Tongue

Weld Mount "Drop Leg" Jack

Extra Durable Epoxy Paint

Step Style Fenders And Fender Supports

Integral Tank Mounting

5200 GVW

Adjustable Height 2-5/16 Inch Ball Coupler

Electric Braking System

6 Lug Chrome Wheels Standard

Udor Super Duty Pumps

Triplex Ceramic Plunger Pump

Low RPM Gearbox

Long Lasting U-Seal Design

Water Bypass Pulse Port, Remotely Controlled

Tapered Roller Bearings

**Bronze Connecting Rods** 

5 Year Limited Warranty Through UDOR USA

Jetting Nozzles

4 Included Nozzles Matched For Flow, Pressure, And Hose Length

Penetrator, 1 Front/4 Rear (20deg)

Flusher, 6 Rear (35deg.)

De-Icer, 3 Front (10deg.) /6 Rear (35deg)

Rotator, 2 Rear On Rotating Element

6 Inch Nozzle Extension Pipe

Hose End Adapter For Connecting JNW Accessories

Stainless Steel Construction

Includes Nozzle Storage Box And Orifice Cleaner

Jetting Reel

Heavy Duty Bearing Supported Reel

Large Diameter Drum, 600ft. 1/2" Capacity

1 Piece Flow Through Axle Design

Welded Frame

Heavy Duty 1/2 Hp High Torque Motor

Variable Speed Control

Power Wind And Unwind Standard

Elevated Mounting For Operator Comfort

Dirty Tools Basket Below Reel

Pivoting Hose Guide With Nylon Rollers

Storage Compartment

Heavy Gauge Steel Construction

Convenient Location
Secure Lockable Handles
60 Inch Wide With Single Drop Door

Warranty Information