



SPALYS43
Design by Ryosuke Fukusada


Collection consisting of aluminium suspended lamps.
Available in several colours and sizes.

Typology: SUSPENSION LAMP

Ratings

- Built in line voltage **LED** module
- CCT 3000 K
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off dimmable trailing edge
- Die cast aluminium body, painted
- Opalescent diffuser

Product code composition




ALYSOID					
Type	Article	Colours	Catene / chains	Source	
SP	ALYS 43	AN anthracite grey wrinkled	NI black polished nickel	LED 20W - diffused beam 3000K available on request 2700K	
			OT natural brass		

IP20 CRI90 220-240VAc **LED** ~1800 lm 90 lm/W

example composition code | SP | ALYS43 | AN | NI | LED

Available colors



OT
Anthracite grey and natural brass

NI
Anthracite grey and black polished nickel

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER _____ NOTES _____

SPALYS43AN__LED

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.