



# Technical Data

PRODUCT TECH

©2011 Torco

## T-4 4-STROKE MOTOR OILS (PETROLEUM)

SAE: 10W/40 & 20W/50

### >>Description

Torco T-4 4-Stroke Motor Oil is a highly refined petroleum lubricant designed specifically for motorcycle and ATV engines. It utilizes an exclusive blend of additives and polymer systems that resist high shock loads, high temperatures, shearing and eliminates deposits. T-4 is formulated to remain stable under peak operating temperatures and will provide excellent protection for integrated transmissions. The non-friction modified T-4 formula focuses on positive clutch engagement under high acceleration and deceleration loads.

### >>Features

- >Premium grade petroleum formula
- >Excellent thermal and shear stability
- >Non-friction modified formula
- >Provides smooth, positive clutch activation
- >Excellent anti-wear and deposit free performance

### >>Application

For air cooled or liquid cooled 4-cycle engines of all sizes found on motorcycle, scooter and ATV applications.

Exceeds manufacturer warranty requirements. Exceeds API SG / JASO-MA.

### >>Typical/Test Data

<b>SAE Grade</b>	<b>ASTM#</b>	10W/40	20W/50
<b>Appearance</b>	<b>Visual</b>	Amber	Amber
<b>Viscosity @ 100°C</b>	<b>D-445</b>	15.8	20.31
<b>Viscosity @ 40°C</b>	<b>D-445</b>	118	173
<b>Pour Point, °C</b>	<b>D-97</b>	-28	-20
<b>Flash Point, °C</b>	<b>D-92</b>	215	223

### >>Directions

Follow manufacturer's fill level requirements. Compatible with other petroleum and synthetic lubricants.

### >>Package Sizes / P/N

<b>SAE Grade</b>	10W/40	20W/50
<b>1-Liter (1.056 US QT)</b>	T611040CE	T612050CE
<b>12/1-Liter Case</b>	T611040C	T612050C
<b>5 Gallon Pail</b>	T611040E	T612050E
<b>55 Gallon Drum</b>	T611040B	T612050B

