

MiR200 for automation of in-house transport solutions

MiR200 EN 03 2017

Specifications	
Designated use	Mobile robot for transport tasks within industry, logistics and healthcare
Dimensions	
Length	890 mm
Width	580 mm
Height	352 mm
Weight (without load)	62.5 kg
Load surface	600 x 800 mm
Color	RAL 7011
Payload	
Robot payload	200 kg (maximum 5% incline)
Towing capacity	500 kg (see separate MiRHook 200 data sheet)
Speed and performance	
Running time	10 hours or 15 km
Maximum speed	Forwards: 1.1 m/s (4 km/h) / backwards: 0.3 m/s (1 km/h)
Turning radius	520 mm (around center of robot)
Positioning accuracy	+/-50 mm of position, +/-10 mm to docking marker
Traversable gap and sill tolerance	20 mm
Power	
Battery	Li-NMC, 24 V, 40 Ah; charging time: up to 3 hours (0-80%: 2 hours)
Internal charger	Input: 100-230 V ac, 50-60 Hz / Output: 24 V, max 15 A
Environment	
Ambient temperature range	+5°C to 50°C (humidity 10-95% non-condensing)
IP class	IP 20
Communication	
WiFi	Dual-band wireless AC/G/N/B
Bluetooth	4.0 LE, range: 10-20 m
I/Os	USB and Ethernet
Safety sensors	
SICK laser scanners S300 (2 pcs.)	360° visual protection around robot
3D camera Intel RealSense™	Detection of objects ahead 50-500 mm above floor
Ultrasonic scanners (4 pcs.)	Detection of transparent objects ahead, e.g. glass doors
Safety compliance and approvals	EN 1525, PLd cat. 3, ESD approved and CE certified
Top module	
Max. height from floor to top	1800 mm
Center of gravity	Lower than 900 mm above the floor

Copyright © 2017 Mobile Industrial Robots ApS. All rights reserved

Mobile Industrial Robots ApS
Emil Neckelmanns Vej 15F
DK-5220 Odense SØ

+45 20 377 577
mail@mir-robots.com
www.mir-robots.com



MiR200 dimensions

