


# LED EXPLOSION PROOF LIGHT

Explosion Proof Outdoor LED Luminaire (D SERIES)




Our D Series LED Explosion Proof Light can provide general illumination in hazardous locations such as oil refineries, gasoline loading docks, distilleries, pumping stations, mines, vessels, paint manufacturing plants and other high humidity, high temperature, dusty locations.



**BUY NOW**



## DIMENSIONS



## FEATURES

- Copper free aluminum
- High vibration resistance
- IP67 Waterproof
- Reduces energy consumption up to 60%
- Cree LED Chips
- Mean Well driver
- Wide and narrow optics for uniform illumination
- Surface mounting and pendant installations
- 5 Year Manufacturer's Warranty

## CERTIFICATIONS & RATINGS



- NEMA 4X, IP66
- UL1598/UL1589A/UL844
- CSA C22.2 No. 137/No.250.0
  - Class I, Division 1, Groups C,D
  - Class I, Division 2, Groups A,B,C,D
  - Class II, Division 1, Groups E,F,G
  - Class II, Division 2, Groups E,F,G
  - Class III
- IECEx
- ATEX
- L70

## COMMON TECHNICAL DATA

Color Temperature	4000K to 5700K
CRI	> 70
Beam Angle	40°, 60°, 90°, 120°
Operation Temperature	-40°C to 60°C
Efficiency	More than 140 LPW
Input Voltage	AC100-277V/200-480V
Frequency	50-60Hz
Power Factor	More than 0.90
Rated Life	150,000 hours
LED Type	Cree LED Chips



D SERIES



## WARRANTY

This product has a warranty for a period of 5 years from the date of purchase. The warranty is invalid in the case of improper installation, tampering, or removal of the Q.C. date label. Installation in an improper working environment or installation not according to the current edition of the National Electric Code also invalidates the warranty. Should this product fail during the warranty period, it will be replaced free of charge, subject to correct installation and return of the faulty unit. James® does not accept responsibility for any installation costs associated with the replacement of this product. This warranty is in addition to the statutory rights in the country of purchase. James® reserves the right to alter specifications without prior notice.

# LED EXPLOSION PROOF LIGHT

Explosion Proof Outdoor LED Luminaire (D SERIES)




## PRODUCT SPECIFICATION

Product Number	Wattage	Color	Beam Angle	Lumens	Input Voltage
JLX-80W DXYZA	80W	4000K-5700K	40°, 60°, 90°, 120°	11,200	AC100-277V/AC200-480V
JLX-100W DXYZA	100W	4000K-5700K	40°, 60°, 90°, 120°	14,000	AC100-277V/AC200-480V
JLX-120W DXYZA	120W	4000K-5700K	40°, 60°, 90°, 120°	16,800	AC100-277V/AC200-480V
JLX-150W DXYZA	150W	4000K-5700K	40°, 60°, 90°, 120°	21,000	AC100-277V/AC200-480V
JLX-200W DXYZA	200W	4000K-5700K	40°, 60°, 90°, 120°	28,000	AC100-277V/AC200-480V

## ORDERING GUIDE

Company Code	80W/100W/120W/150W/200W Wattage	D Series	D/N X= Dimming Options	4000K-5700K Y= CCT	40°, 60°, 90°, 120° Z= Beam Angle	C/Blank A= Long Glass Cover/ None
--------------	------------------------------------	-------------	---------------------------	-----------------------	--------------------------------------	--------------------------------------

## LIGHT DISTRIBUTION



## CAUTION

- Risk of fire- make sure power is OFF before installation.
- Risk of electric shock- make installation with gloves.
- All wiring needs to be performed per National Electrical Code and local code by a qualified electrician.
- These lamps can be used with a light dimmer.
- High temperatures inside luminaire. Make certain line voltage corresponds with ballast's primary voltage.
- If the lamp or luminaire exhibits undesirable operation (i.e. buzzing, flickering, etc.), immediately turn off power and remove the lamp from luminaire and contact manufacturer.
- Luminaires should not be installed in narrow space to guarantee enough air convection.
- Do not make mass installation before sample testing.