



1 TOUCH ECO PARKLIGHT & HEADLIGHT CONTROL MODULE

Use the ECO Push Button Park/Headlight Module to control your Park Lights & Headlights with a push of a button!

A great tool to use with one of our etched Billet Buttons



IMPORTANT INFORMATION!

- 1** You must use relays on ALL outputs except for Status LED output.
- 2** All outputs are negative trigger.

Unit Operation

Park Light Output

1. Press button (Blue Input) for 1 second to turn on Park lights output. Button LED will flash.
2. Press button again (Blue Input 1) for 1 second to turn off Park Lights.

Head Light Output

1. Press button (Blue Input) for more than 3 seconds. Headlights will activate. Button LED will stay solid.
2. To turn Headlights off, Press & hold button (Blue Input 1) for more than 3 seconds.

Settings

- A. Press button 1 for five seconds to enter programming mode. Digital display will illuminate.
- B. Press buttons 2 or 3 to scroll through modes. Press button 1 to choose the desired mode to change. (1 through 9) the chart to the right shows recommended settings.
- C. Press buttons 2 to 3 to adjust selected mode value. The chart to the right shows recommended settings.
- D. Press button 1 to save your settings.
- E. Repeat steps 2 through 4 until all modes have desired settings.
- F. Wait for 15 seconds to allow the unit to auto exit program mode.
- G. Push the button to test operation. Adjust mode settings until you are satisfied.

Recommended Defaults

1. 2.5
2. 0.0
3. 0.0
4. 0.0
5. 0.5
6. 0.0
7. 0.0
8. 0.0
9. 0.0

