



Fagor Kore 700 Bench Top Chrome Gas Griddle - FT-G705CL

Quick Overview

- Natural Gas
- Stamped surface tops manufactured in 1.5 mm thick AISI-304 stainless steel.
- Laser-cut joints, automatic welding and polishing. Hidden screws.
- Rapid reaction and recovery times of the fry-top temperature.
- The fry tops are welded to the stamped surface top.

Description

Bench Top Chrome Gas Griddle NG - FT-G705CL

- Natural Gas
- Stamped surface tops manufactured in 1.5 mm thick AISI-304 stainless steel.
- Laser-cut joints, automatic welding and polishing. Hidden screws.
- Rapid reaction and recovery times of the fry-top temperature.
- The fry tops are welded to the stamped surface top.
- The stamped shell and its rounded edges and corners make cleaning much easier.
- The fry top is tilted towards the front to make it easier to collect grease and liquids.
- Fitted with an opening to collect cooking grease and a tray to store it which has capacity to store up to 2 litres depending on the model.
- Optional anti-splash side and rear guards, easy to remove.
- High-temperature enamelled cast iron flue protector.
- Access to components from the front.
- Machines with IPX5 grade water protection.
- Model with smooth hot plates.
- 15 mm thick mild steel fry tops which are quick-heating and high power.
- Version with 50-micron thick chrome surface for the three hot plate types.
- Gas heated model with high efficiency burners (separate burners for whole-module models).
- Model with thermostatic temperature control (between 100 and 300 ° C).
- Burner ignition through electronic spark igniter. Therefore, the gas models do not need electricity for installation. With an access tube for manual ignition.
- Whole-module fry tops have two separate heating areas.

SUPPLIED ACCESSORIES:

- 19045083 Fry-top scraper for Kore generation 1

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Net Weight (Kg)	35
Width (mm)	400
Depth (mm)	730
Height (mm)	290
Packing Width (mm)	440
Packing Depth (mm)	820
Packing Height (mm)	510
Power	25mj/h; 7.5kW
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice