



## Fagor Kore 700 Gas Pasta Cooker with 4 Baskets - CP-G7226

### Quick Overview

- Surface tops manufactured in 1.5 mm thick AISI-304 stainless steel.
- Laser-cut joints, automatic welding and polishing. Hidden screws.
- 1.5 mm thick AISI-316L stainless steel wells built into the surface top.
- The well is filled through the inlet solenoid valve with a two-position switch: average and high-speed filling.
- Well drainage through a mechanical ball valve which is resistant to high temperatures and has a safety overflow.

### Description

#### Gas Pasta Cooker with 4 Baskets - CP-G7226

- Surface tops manufactured in 1.5 mm thick AISI-304 stainless steel.
- Laser-cut joints, automatic welding and polishing. Hidden screws.
- 1.5 mm thick AISI-316L stainless steel wells built into the surface top.
- Wells that suit with different arrangements and measures of baskets.
- The well is filled through the inlet solenoid valve with a two-position switch: average and high-speed filling.
- Well drainage through a mechanical ball valve which is resistant to high temperatures and has a safety overflow.
- Automatic safety system to stop the current if the water runs out.
- Controls with a protective support base and system to prevent water infiltration.
- Access to components from the front.
- Stainless steel feet with adjustable height.
- Machines with IPX5 grade water protection.
- High-performance stainless-steel burner located outside of the well with a combustion chamber that enables heating of the base and sides of the well (up to the minimum filling level).
- Burner ignition through electronic spark igniter. With an access tube for manual ignition.
- Heating controlled through safety valve.
- Two wells of dimensions GN-2/3, with 26 litres capacity.
- Standard provision: Four 1/3 type baskets.

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

## Your Shipping Specifications

---

|                     |   |
|---------------------|---|
| Net Weight (Kg)     | 89  |
| Width (mm)          | 800   |
| Depth (mm)          | 730   |
| Height (mm)         | 850   |
| Packing Width (mm)  | 840   |
| Packing Depth (mm)  | 822   |
| Packing Height (mm) | 1255  |
| Power               | 50/60Hz; 230V - 1N; 2A; 0.1 kW  |
| Warranty            | 2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice |