



## Single Tank Induction Fryer - IF3500S

### Quick Overview



- Stainless Steel body
- LED display
- Timer (0 - 120 min)
- Fast recovery
- Temperature setting: 60 °C, 80 °C, 100 °C, 120 °C, 130 °C, 140 °C, 150 °C, 160 °C, 170 °C, 180 °C, 190 °C
- Oil drainage
- Touch control
- Tank Capacity: 8L

### Description

Digital induction fryer provides much precisely controlled temperature range within 2 °C, unlike the analog unit which normally has more than 10 °C variance. Induction technology is not only quick, but also very efficient. This device uses energy with an efficiency factor of 90%. That ' s 35% more efficient than conventional electric appliances.

- Stainless Steel body
- LED display
- Timer (0 – 120 min)
- Fast recovery
- Temperature setting: 60 ,80 ,100 ,120 ,130 ,140 ,150 ,160 ,170 ,180 ,190
- Oil drainage
- Touch control
- Tank Capacity: 8L
- With one basket and S/S filter and S/S lid
- Machine Dimensions (WxDxH mm): 288x478x410
- Oil Tank Dimension (WxDxH mm): 248-228 x 300-287.7 x 202
- Basket Dimension (WxDxH mm): 190 x 230 x 145 (measured without handle)

Dimensions (WxDxH mm): 288x478x410

1 Year Parts and Labour Warranty

Your Shipping Specifications

---

Net Weight (Kg)	11
Width (mm)	288
Depth (mm)	478
Height (mm)	410
Packing Width (mm)	565
Packing Depth (mm)	350
Packing Height (mm)	480
Power	240V; 3.5kW; 15A
Warranty	1 Year Return to Base