Super Erecta NK3 Metroseal Wire Shelving



Unique Design: The open wire design of these shelves minimises dust accumulation and allow free circulation of air, greater visibility of store items and greater light penetration



Durable Construction: Super Erecta shelves and posts are constructed of heavy-gauge carbon steel of Type 304 stainless

Superior Finishes: Metro's proprietary epoxy coating, Metroseal 3[™], contains Microban[®] antimicrobial product protection, which protects the epoxy coating from bacteria, mold, mildew and fungus that cause odours, stains and product degradation

Versatile: Super Erecta Shelf® wire shelving can adapt to your changing needs. By using various accessories, hundreds of shelving configurations become possible.

Fast, Secure Assembly: Numbered double groove visual guides feature every 8" (203mm). A patented, tapered split sleeve snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves providing a positive lock. Shelf is assembled in minutes without the use of any special tools.

Strong: Stationary units hold a maximum of 910kg while mobile units have a maximum capacity of 453kg. Maximum weight capacity per shelf evenly distributed: (1219mm or shorter = 363kg; longer than 1219mm = 272kg)

Adjustability: Shelves can be adjusted at 1" (25mm) intervals along the entire length of the post

Shelf Ribs: run front to back, allowing you to slide items on and off shelves smoothly

Shelf Accessibility: Shelves can be loaded/unloaded easily from all sides. This open construction allows maximum use of storage cube.

Adjustable Feet: Bolt levelers compensate for surface irregularities


Accessories: Compatible with the entire system of Super Erecta shelves and accessories
















Super Erecta NK3 Metroseal Wire Shelving









Split Sleeve Locking System

Standard Interchangeable Shelves

Part number includes 4/5 shelves,
4 posts and one bag of split sleeves per shelf

Width (mm)	Length (mm)	4 Tier Unit with 74' 4 Shelf kit Model No.	Approx	5 Tier Unit with 74 5 Shelf kit Model No.	Approx
355	760	NK3.4T74.1430	19.3	NK3.5T74.1430	22.5
355	915	NK3.4T74.1436	20.9	NK3.5T74.1436	24.5
355	1065	NK3.4T74.1442	23.7	NK3.5T74.1442	28
355	1220	NK3.4T74.1448	25.3	NK3.5T74.1448	30
355	1525	NK3.4T74.1460	31.7	NK3.5T74.1460	38
355	1830	NK3.4T74.1472	37.8	NK3.5T74.1472	45
455	760	NK3.4T74.1830	21.3	NK3.5T74.1830	26.3
455	915	NK3.4T74.1836	24	NK3.5T74.1836	29.5
455	1065	NK3.4T74.1842	25.9	NK3.5T74.1842	31.8
455	1220	NK3.4T74.1848	28.6	NK3.5T74.1848	35.4
455	1370	NK3.4T74.1854	33.2	NK3.5T74.1854	40.5
455	1525	NK3.4T74.1860	37.2	NK3.5T74.1860	46.3
455	1830	NK3.4T74.1872	42.6	NK3.5T74.1872	53.1
535	915	NK3.4T74.2136	26.8	NK3.5T74.2136	33.1
535	1065	NK3.4T74.2142	29.5	NK3.5T74.2142	36.7
535	1220	NK3.4T74.2148	32.2	NK3.5T74.2148	39.9
535	1370	NK3.4T74.2154	35.5	NK3.5T74.2154	44.5
535	1525	NK3.4T74.2160	39.9	NK3.5T74.2160	49.4
535	1830	NK3.4T74.2172	44.5	NK3.5T74.2172	55.3
610	760	NK3.4T74.2430	25.9	NK3.5T74.2430	32.2
610	915	NK3.4T74.2436	29.5	NK3.5T74.2436	36.7
610	1065	NK3.4T74.2442	32.7	NK3.5T74.2442	40.4
610	1220	NK3.4T74.2448	35.8	NK3.5T74.2448	44.5
610	1370	NK3.4T74.2454	39.5	NK3.5T74.2454	49.8
610	1525	NK3.4T74.2460	44.5	NK3.5T74.2460	55.3
610	1830	NK3.4T74.2472	54.4	NK3.5T74.2472	67.6

SiteSelect Posts

Stationary post height includes leveling bolt for uneven floors

NOTE: Special length posts are available upon request. Consult your Metro representative.




Stationary

Height (mm)	Weight (kg)	•		
1385	1.4	54PK3		
1890	1.8	74PK3		
2200	2.3	86PK3		



Г	VI	\mathbf{c}	h	п	0	(For	LICA	with	etam	castors)
	▼ ■	•	v		\sim	11 01	use	VVILII	SIGIII	Casidisi

	Height	Weight	Super Erecta		
	(mm)	(kg)	Model No.		
Ī	1570	1.6	63UPK3		



Foot Plates

 Use to bolt units to the floor, or when a broader, more stable foot is desired. Foot plates also help to protect floors by distributing the point load of the shelving unit across a larger contact point



- Foot plates (completely tightened) add 3mm to the specified heights of each stationary post on the table
- Zinc Model no. 9993Z
- Stainless Steel Model no. 9993S

"S" Hook

- Used to add on shelving units with only two posts required. Order two per shelf level.
- Model no. 9995Z







Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: 01 - 28/07/2021

www.stoddart.com.au www.stoddart.co.nz

