

EX2

TRADITIONAL ESPRESSO

EX2

Versions

- EX2 MINI 1GR CONTROL
- EX2 MINI 2GR CONTROL
- EX2 2GR CONTROL

EX2

Features



EX2 perfectly combines the heritage from CREM traditional espresso machines with a contemporary design within the EX line.

Its optimized but robust body includes Expobar well known reliable and consistent hydraulics to offer a wide range of espresso-based drinks. The EX2 is, in this sense, the best choice for those businesses looking for a smart balance between budget and performance.

The EX2 comes in three versions -**2gr, Mini 2gr and Mini 1gr**- to suit any kind of sites.

Main USP's

- Optimized and robust design line
- Expobar well known reliable hydraulics
- 1/2 rotatory knobs
- Electronic pre-infusion and pre-infusion chamber group head
- Ergonomics & Barista flow
- Improved cup tray area
- Ease-of-servicing

CREM*Tech*
inside

Options & Extras

- Take away versions
- Barista lights
- Extra steam wand for 2GR versions




Technical specifications



	EX2 2GR	EX2 MINI 2GR	EX2 MINI 1GR
Height, width, depth	460, 735, 575 mm	460, 515, 575 mm	460, 515, 575 mm
Weight	57 Kg	48 Kg	45 Kg
Power ratings <i>(Power ratings+OPTIONS)</i>	220-240V 1N~ 3350W 50-60Hz	220-240V 1N~ 2800W 50-60Hz	220-240V 1N~ 2800W 50-60Hz
Boiler(s) capacity	11.5 l	6 l	6 l
Operation pressure	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar
Pressure switch control	✓	✓	✓
PID control	-	-	-
Water connection	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread
Height group	STD / TA (O)	STD / TA (O)	STD / TA (O)
Volumetric dosing (5 keypad button)	✓	✓	✓
Volumetric dosing + group display	-	-	-
Group flush button	✓	✓	✓
Steam wands + HW tap	1+1	1+1	1+1
Extra steam wand	O	-	-
Auto hot tap water dose	O	-	-
½ turn rotary taps	✓	✓	✓
Lever taps	-	-	-
Cool touch steam wands	-	-	-
Built-in rotatory pump	✓	✓	✓
Pre infusion chamber group head	✓	✓	✓
Electronic pre infusion	✓	✓	✓
Jet hole	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm	STD group height: 3.5 / 2.5 mm (O) TA group: 2.5 mm
Pressure gauge	60 mm single	60 mm single	60 mm single
High feet / Hidden feet	-	-	-
Colours	Light grey	Light grey	Light grey
Knob finishing	Black	Black	Black
Body covers	-	-	-
Barista lights	O	O	O
Auto cleaning group cycle	✓	✓	✓
ECO mode	-	-	-
Auto On/OFF	-	-	-
Optional power cord (Country Kit)	STD: Type F (1Ph) O: 1Ph (Type I AUS 15A, 16A BareW)	STD: Type F O: 1Ph (Type I AUS 10A, Type G 13A)	STD: Type F O: 1Ph (Type I AUS 10A, Type G 13A)
Single+Double portafilter	1+2	1+2	1+1
Extra portafilters	-	-	-

NOTE: Please check your regional price list for available versions/options and part numbers.

INSTALLATION NOTE: Please refer to the User Manual and the Technical Manual.



Welbilt reserves the right to make changes to the design or specifications without prior notice.