

High hard wax
content

Specially designed
for parquet floors



Fluid texture



Quick drying



Liquid Wax



PRODUCT DESCRIPTION

- Blanchon **Liquid Wax** is designed for application on floors and particularly wood and parquet floors.
- **Liquid Wax** is fluid and its high wax content provides strong waxing power.
- Colours available: natural, clear.

SURFACE PREPARATION

- Prepare new or existing wood floors by sanding (refer to the Appendix* for details on wood floor sanding).
- Remove all traces of dust.
- The wood floor must be completely clean and dry with, in general, a moisture content less than 10%. Do not use detergents or whiteners.
- **Liquid Wax** may be applied over a coat of Blanchon Preplast Primer or Blanchon S.O. Primer, which limits the penetration of **Liquid Wax**, thus making polishing easier.

DIRECTIONS FOR USE

- Only use in well ventilated areas. Do not allow plants and aquariums to come into contact with the solvent vapours.
 - Pour the product onto the floor.
 - Spread it out evenly with a cotton rag or a waxing brush.
 - Allow to dry, then polish with light pads (beige or white) or a woollen cloth. A sheen is quickly and efficiently obtained if a buffing machine is used.
 - Sometimes two or three coats are necessary to obtain a very high quality finish and resistance.
- Note: **Liquid Wax** naturally congeals below 12°C. Simply place the product in a warm location for a few moments to liquefy it (not in direct contact with flames).

Cleaning of tools

- Clean tools immediately after use with Blanchon Odourless Thinner or Turpentine. Do not empty into drains.
- Seal the container properly after use.

DRYING TIMES

- Dust-free: 2 to 4 hours.
- Before polishing: 8 to 16 hours under normal conditions of use (temperature 20°C, relative humidity 65%, well ventilated areas).

NB: always allow high quality waxes to dry properly before polishing. Waxes like this must be thoroughly dry in order to obtain the best lustre from polishing.

COVERAGE

- 15 to 25 m² per litre, depending on the absorption of the wood.

MAINTENANCE

- Vacuum regularly to remove dust.
- **Liquid Wax** is maintenance free.
- As soon as the waxed floor loses its sheen, polish it with a buffing machine (beige or white pad) or a woollen cloth to restore its appearance.
- Carry out this operation regularly with a few drops of **Liquid Wax** to maintain floor protection and shine (do not wait until the wax is worn through).
- Do not allow water to stand on the waxed floor.
- Treat small stains with N° 000 steel wool and re-wax the area.

Blanchon

Liquid Wax

TECHNICAL DATA

USE	Liquid wax for parquet floors, wood floors and woodwork
RESIN TYPES	Natural and synthetic waxes
DENSITY	0.80 [at 20°C, as per NF T 30020]
FLUIDITY	32 seconds (ISO n° 3 cup at 23°C)
REGULATORY INFORMATION	Refer to the relevant Material Safety Data Sheets [also available on www.blanchon.com www.quickfds.com]

*APPENDIX: SANDING A WOOD FLOOR USING A MACHINE

- This is done using a special floor sander, with an edge sander for the edges and a scraper for the corners.
- The floor sander should be used in the direction of the light, or better still, in the direction of the wood grain.
- Work in even, regular "sweeps" to ensure that the entire surface is done in an identical manner.
- 1st pass: coarse grit (24, 30 or 36) to expose the bare wood and level it.
- 2nd pass: medium grit (50 or 60) to get a smooth, even surface.
- 3rd pass: fine grit (100 or 120) to obtain a good finish.
- Do all the edges of the room with the edge sander and scraper.
- Polishing with a buffing machine fitted with an abrasive mesh (80 or 120) ensures that the surface is perfectly prepared, especially in the case of flooring that has alternating lines (mosaics, chevrons, herringbone pattern, basket weave pattern, etc.).
- Remove all dust carefully, using a powerful vacuum cleaner, from the area to be lacquered, including any skirting boards, window ledges and radiators.

Technical Data Sheet issued on the 10.05.2012.

The information provided in this Technical Data Sheet is given in good faith for information purposes only. In no case whatsoever can this information be considered as a guarantee given by us nor engage our responsibility when our products are used. Since we are constantly striving to improve our products, the information given here may be subject to modification without prior notice.

This Technical Data Sheet cancels and supersedes all previous versions.

Respect
for people and
the environment



www.blanchon.com

28 rue Charles Martin - BP 105
69192 SAINT-FONS CEDEX - FRANCE
Tél. 04 72 89 06 00 - Fax 04 78 70 07 18
Export Lines: Tel: (0033) 472 89 06 09
Fax: (0033) 472 89 06 02

Blanchon

BLANCHON S.A. - Est. 1832 - A stock company with a board of directors and a supervisory board, with a registered capital of € 4 258 258
390 112 886 RCS LYON - APE 2030 Z - E-mail: info.uk@blanchon.com
Internet : www.blanchon.com