



ZONEMASTER™

MOTORIZED ADJUSTABLE DAMPER

Control airflow in an HVAC system or fresh air intake

- Adjustable close or open position range stops
- Shipped as power closed/spring return or power open/spring return
- Available in 6", 8", 10" & 12" diameters
- Male crimped and female uncrimped ends to connect to rigid or flexible round duct
- 20 gauge blade closes against gasket for minimal leakage
- Simple easy-to-wire, two wire installation
- Safe, UL listed 24VAC/20 VA plug-in transformer included
- Tremendous energy saver
- Free-wheeling coupling for long life
- 8" long metal housing
- Three year limited warranty




Model	Duct Diameter	Power "OFF"	Housing Gauge
ZC206	6"	Closed	25
ZO206	6"	Open	25
ZC208	8"	Closed	25
ZO208	8"	Open	25
ZC210	10"	Closed	22
ZO210	10"	Open	22
ZC212	12"	Closed	22
ZO212	12"	Open	22



24 VAC, 1 RPM, 60 Hz, 6 Watts
 Maximum Torque 78 in.-oz.
 2 Wire Synchronous Hysteresis Motor

SUNCOURT INC.
 Durant, IA 52747-0040
 1.800.999.FANS

WWW.SUNCOURT.COM



**Assembled
 in USA**

Copyright© 2020
 CATDamper-0420