

# **EQUALIZER® EQ2**REGISTER BOOSTER™

### MOST VERSATILE & ENERGY EFFICIENT REGISTER BOOSTER ON THE MARKET!

Boosts airflow to problem areas, giving you the comfort your family deserves. The Equalizer's quiet and powerful fan works to pull extra air out of weak registers, increasing airflow by up to 80%!



# REGISTER BOOSTER



- Simple and safe solution for rooms that are too hot or cold
- Fits any register that is 6" x 12" or smaller
- Can be installed in floor or wall registers
- Low cost/low energy solution
- Easy plug and play installation
- Built-in temperature sensor
- Engineered for maximum airflow
- Works automatically with forced air systems

Model	Unit Weight	Unit Size	Volts	CFM	Watts	DBA	Cord Length
HC300	2.15 lbs.	12" × 6-1/4"x3-1/4"	12Vdc 500 mA	125	20	50	6′

CATHC300-1220



#### **MOST VERSATILE & ENERGY EFFICIENT REGISTER BOOSTER ON THE MARKET!**

The Flush Fit® Register Booster™ boosts heated or cooled air to a room to improve circulation and comfort. The powerful fan works to pull extra air out of weak registers, increasing airflow by up to **85%!** A simple and safe solution for rooms that are too hot or too cold.



#### SMART REGISTER BOOSTER MODEL: HC500-B





- Automatically turns on/off with HVAC system.
- · Patent pending intelligent technology delivers hands off auto functionality with no seasonal temperature settings necessary.
- 5 fan speed settings.
- · Set-up in seconds. Just plug-in, set in the register and enjoy increased comfort.
- · Quiet operation.
- Booster fan fits flush into floor and wall registers that are 4" x 10" for a clean. contemporary look.
- · Can be installed in floor or wall registers.

Booster & adapter plate also sold together - HC500-WPL

١	Model	Unit Weight	Unit Size	Volts	CFM	Running Watts	DBA	Cord Length
	HC500-W	1.45 lbs.	11-5/8" x 5-5/8"	12Vdc 500 mA	Up to 132	Up to 3.9	Up to 53	6′

CATHC500-B-1220



### MOST VERSATILE & ENERGY EFFICIENT REGISTER BOOSTER ON THE MARKET!

The Flush Fit® Register Booster™ boosts heated or cooled air to a room to improve circulation and comfort. The powerful fan works to pull extra air out of weak registers, increasing airflow by up to 85%! A simple and safe solution for rooms that are too hot or too cold.



# SMART REGISTER BOOSTER





- Automatically turns on/off with HVAC system.
- Patent pending intelligent technology delivers hands off auto functionality with no seasonal temperature settings necessary.
- 5 fan speed settings.
- Set-up in seconds. Just plug-in, set in the register and enjoy increased comfort.
- · Quiet operation.
- Booster fan fits flush into floor and wall registers that are 4" x 10" for a clean, contemporary look.
- Can be installed in floor or wall registers.

Model	Unit Weight	Unit Size	Volts	CFM	Running Watts	DBA	Cord Length
HC500-BPL	1.45 lbs.	11-5/8" x 5-5/8"	12Vdc 500 mA	Up to 132	Up to 3.9	Up to 53	6′

**QUALITY | COMFORT | CONTROL** 

CATHC500-BPL-1220



#### **MOST VERSATILE & ENERGY EFFICIENT REGISTER BOOSTER ON THE MARKET!**

The Flush Fit® Register Booster™ boosts heated or cooled air to a room to improve circulation and comfort. The powerful fan works to pull extra air out of underperforming registers, increasing airflow by up to 85%! A simple and safe solution for rooms that are too hot or too cold.



#### SMART REGISTER BOOSTER MODEL: HC500-W





- Automatically turns on/off with HVAC system.
- · Patent pending intelligent technology delivers hands off auto functionality with no seasonal temperature settings necessary.
- 5 fan speed settings.
- · Set-up in seconds. Just plug-in, set in the register and enjoy increased comfort.
- · Quiet operation.
- Booster fan fits flush into floor and wall registers that are 4" x 10" for a clean. contemporary look.
- · Can be installed in floor or wall registers.

Booster & adapter plate also sold together - HC500-WPL

Model	Unit Weight	Unit Size	Volts	CFM	Running Watts	DBA	Cord Length
HC500-W	1.45 lbs.	11-5/8" x 5-5/8"	12Vdc 500 mA	Up to 132	Up to 3.9	Up to 53	6′

CATHC500-W-1220



### MOST VERSATILE & ENERGY EFFICIENT REGISTER BOOSTER ON THE MARKET!

The Flush Fit® Register Booster™ boosts heated or cooled air to a room to improve circulation and comfort. The powerful fan works to pull extra air out of weak registers, increasing airflow by up to 85%! A simple and safe solution for rooms that are too hot or too cold.



# SMART REGISTER BOOSTER





- Automatically turns on/off with HVAC system.
- Patent pending intelligent technology delivers hands off auto functionality with no seasonal temperature settings necessary.
- 5 fan speed settings.
- Set-up in seconds. Just plug-in, set in the register and enjoy increased comfort.
- · Quiet operation.
- Booster fan fits flush into floor and wall registers that are 4" x 10" for a clean, contemporary look.
- Can be installed in floor or wall registers.

Model	Unit Weight	Unit Size	Volts	CFM	Running Watts	DBA	Cord Length
HC500-WPL	1.45 lbs.	11-5/8" x 5-5/8"	12Vdc 500 mA	Up to 132	Up to 3.9	Up to 53	6′

**QUALITY | COMFORT | CONTROL** 

CATHC500-WPL-1220





#### **MOST VERSATILE & ENERGY EFFICIENT REGISTER BOOSTER ON THE MARKET!**

The Equalizer® EZ8 boosts heated or cooled air to a room to improve circulation and comfort. The powerful fan works to pull extra air out of weak registers, increasing airflow by up to 300%! A simple and safe solution for rooms that are too hot or too cold.



#### SMART REGISTER BOOSTER MODEL: HC600 / HC600-WK



- Automatically turns on/off with HVAC system.
- · Patent pending intelligent technology delivers hands off auto functionality with no seasonal temperature settings necessary.
- · 8 fan speed settings.
- Set-up in seconds. Just plug-in, set on the register and enjoy increased comfort.
- Quiet operation.
- Fits any register that is 6"x12" or smaller.
- · Can be installed on floor or wall registers. (Wall mount kit sold separately)

Booster & wall mount also sold together - HC600-WK

Model	Unit Weight	Unit Size	Volts	Cord Length
HC600 / HC600-WK	1.50 lbs.	14-7/32" x 6-27/32"	12Vdc 500 mA	6′

FAN SPEED	1	2	3	4	5	6	7	8
CFM	63	88	110	141	163	179	191	203
DBA	<50	<50	<50	53.6	55.5	57.7	59.5	61.7
WATTS	1.1	1.8	2.6	4.2	5.8	8.0	10.2	12.3
*ROOM SQ. FT.	65-95	95-130	115-165	150-210	175-240	190-265	200-285	215-305

\*Assuming 8' ceiling height

CATHC600-1220