







NIKOLATESLA ONE

83 x 51x 21 cm Duct-out / Re-circulating Black glass, white glass

The product, winner of the 25th ADI Compasso d'Oro award, combines cutting-edge downdraft technology with Elica's signature state-of-the-art design. The Direct Slider interface allows the various cooking and extraction areas to be controlled simply and intuitively.





















ASPIRATION SYSTEM

Model Duct-out Re-circulating Controls ONE HP Individual touch control Individual touch control Controls ONE Circular touch control Circular touch control Speeds 9 speeds + boost 9 speeds + boost Booster airflow 536 m³/h 647 m3/h Suction speed 5.1 m/s 5.1 m/s 65 dBA Noise level 59 dBA 160 W Total power absorption 160 W Duct size 150 mm 150 mm Energy class A+ Aluminium grease filter Included Included Ceramic filter Included













OPTIONAL ACCESSORIES

Replacement Ceramic KIT0120952

filter

* Not used for Duct-out hoods

INDUCTION HOB

7,4 kW Absorption Frequency 50 - 60 Hz Voltage 220 - 240 V Zone number ONE HP 4 (2,1-3,7 kW) - 180x200 mm Zone number ONE 1 (2,1 - 3 kW) - 180x200 mm 1 (1,6 - 1,85 kW) - 180x200 mm 1 (2,3 - 3 kW) - Ø 200 mm 1 (1,4 kW) - Ø 160 mm 2 (ONE HP) - 1 (ONE) Bridge zone

FEATURES

HP.				ONE		
.OCK	TIMER	BRIDGE ZONES	POT DETECTOR	CHILD LOCK	TIMER	BRIE
00					(7-0- 2-0- 0-	55















MODELS NIKOLATESLA HP Black Duct-out PRF0120975 NIKOLATESLA HP Black Re-circulating PRF0120976 NIKOLATESLA Black Duct-out PRF0120977 NIKOLATESLA Black Re-circulating PRF0120978