

# **175mm BACKWARDCURVED CENTRIFUGAL FANS WITH SUPPORT BRACKET**

### **INFORMATION**


IMPELLER:	PA6+GF					
BLADE NO.:	7 BLADES					
BEARING:	NMB BALL BEARING					
LEAD WIRES	AC (AWG20#), DC (AWG22#)					
INSULATION :	CLASS B					
OPERATING TEMPERATURE:	-25°C to 60°C					
SPEED CONTROL	CONTROL INPUT 0~10VDC / PWM					
LIFE EXPECTANCE	50,000 Hours at At 40°C					
SIGNAL OUTPUT	FG (Frequency Generator)					
RoHS COMPLIANCE	Yes.					
IP LEVEL	IP44 (Special IP Rating On Request)					




## SPECIFICATION

MODEL NO.	RATED VAC	OPERATED VOLTAGE (VAC)	SPEED (RPM)	RATED CURRENT (A)	INPUT POWER (W)	Max. M³/H	Air Flow CFM	Max. Static inch-H2O	Pressure PA	Noise Level dB(A)
ECFK225102V2HB-PB	230	184~270	4460	0.85	105	810	476.69	2.98	744	76

### DRAWING:



### PQ CURVE:



Specifications are subject to change without notice. Please visit our website at http://www.sofasco.com for update information.