SBC58BBIIFCFTWINADA



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap cold brew coffee dispenser with panel-ready door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Dual tap commercial grade tap kit includes everything you need to serve flat cold brew coffee on draft

Commercially listed to NSF-7 standards

Product Features:

| Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters |
|---|
| ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings |
| Front-breathing design allows fully recessed installation under counters |
| Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs |
| Customize the front by mounting an overlay panel over the door; seamless look can blend into other cabinetry with no exposed frame. Handle not included (panel size: 23 5/16" W x 28 $1/4$ " H and at least $3/4$ " thick; maximum weight: 10 lbs.) |
| Interior dial thermostat ensures easy temperature management |
| No-frost operation for minimum user maintenance |
| Unit ships with a right hand door swing. For a left hand version, add option LHD upon order |
| Removable two-piece drip tray included for added convenience |
| |

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

 \checkmark





SBC58BBIIFCFTWINADA Specifications:

| Overview | |
|-------------------------------|--------------------|
| Height of Cabinet | 32.0" (81 cm) |
| Height to Hinge Cap | 32.25" (82 cm) |
| Width | 23.63" (60 cm) |
| Depth | 22.75" (58 cm) |
| Depth with door at 90° | 45.0" (114 cm) |
| Capacity | 5.5 cu.ft. (156 L) |
| Defrost Type | Automatic |
| Door | Panel-Ready |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.3 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 110.0 lbs. (50 kg) |
| Shipping Weight | 120.0 lbs. (54 kg) |
| Estimated Time to Ship | 3 to 5 days |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| Kegerator | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Tap Kit | Yes |
| Height with Tap | 47.5" (121 cm) |
| Number of Taps | 2 |
| Thermostat Type | Dial |
| Interior Light | Yes |
| Fan Type | Exterior |
| Refrigerant | R134a |
| Refrigerant Amount | 1.8 oz. |
| High Side PSI | 285.0 |
| Low Side PSI | 88.0 |
| Inter Height | 25.75" (65 cm) |
| Interior Width | 21.0" (53 cm) |
| Interior Depth | 17.75" (45 cm) |
| Compressor Step Height | 6.5" (17 cm) |
| Compressor Step Width | 21.0" (53 cm) |
| | |

| Compressor Step Depth | 5.5" (14 cm) |
|-----------------------|--------------|
| Temperature Range | 34º to 43ºF |
| | |



