

SBC6950SCMTWIN



34.25" x 23.75" x 25" (H x W x D)

Outdoor/indoor commercial nitro-infused dual tap coffee dispenser for built-in or freestanding use, with complete tap kit, digital thermostat, and 304 grade stainless steel exterior

Highlights:

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro-infused cold brew drafts

Product Features:

Dispenses both flat and nitro-infused coffee Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro-infused drafts from two cornelius kegs

Commercially approved ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings

Weatherproof design Solid construction allows placement in the outdoors

Built-in capable Front-breathing design allows fully recessed installation under counters

Full-sized coffee dispenser Large interior can accept up to three cornelius kegs

Complete tap kit Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs

Dual tap system Twin style draft tower allows you to serve from two cornelius style kegs

Stainless steel exterior Door and cabinet are wrapped in 304 grade stainless steel for lasting durability in the outdoors

Professional handle Blade style handle in brushed stainless steel matches many popular styles of cabinetry and grill details



SBC695OSCMTWIN Specifications:

| Overview | |
|----------------------------|-----------------------|
| Height of Cabinet | 34.25" (87 cm) |
| Width | 23.75" (60 cm) |
| Depth | 25.0" (64 cm) |
| Depth with Handle | 26.88" (68 cm) |
| Depth with door at 90° | 47.75" (121 cm) |
| Capacity | 6.04 cu.ft. (171 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Stainless Steel |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Amps | 1.3 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 108.0 lbs. (49 kg) |
| Shipping Weight | 113.0 lbs. (51 kg) |
| Estimated Time to Ship | 3 to 5 days |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| Keerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Tap Kit | Yes |
| Height with Tap | 50.38" (128 cm) |
| Number of Taps | 2 |
| Thermostat Type | Digital |
| Interior Light | Yes |
| Fan Type | Interior and Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 1.76 oz. |
| High Side PSI | 220.0 |
| Low Side PSI | 43.0 |
| Inter Height | 27.0" (69 cm) |
| Interior Width | 20.38" (52 cm) |
| Interior Depth | 21.25" (54 cm) |
| Compressor Step Height | 5.5" (14 cm) |
| Compressor Step Width | 9.63" (24 cm) |

| | |
|-----------------------|-----------------|
| Compressor Step Depth | 2.5" (6 cm) |
| Wheel Qty | 4 |
| Surface | Stainless Steel |
| Temperature Range | 32° to 50°F |

