



FLEXBAR DIGITAL MULTI-GAGE™ FEATURING DIGI-MET® TECHNOLOGY



A Multi-Function, Precision Measuring Instrument
with Virtually Unlimited Application Adaptability
TWO MODELS - MEASURING RANGES UP TO 25" (625mm).



Left: Flexbar Multi-Gage with various measurement accessories. Multi-Gage will accept any 4-48 threaded mounting hardware. Shown with flip-up & permanent depth stops for accurate alignment.

The FLEXBAR DIGITAL MULTI-GAGE SYSTEM provides a highly effective and economical solution for a myriad of measurement applications including:

- General I.D. & O.D. Measurements.
- Tapers, Chamfers.
- Deep Measurements.
- Center-to-Center.
- Grooves and Recesses.
- Many other applications.

The Flexbar Multi-Gage utilizes a Preisser DIGI-MET electronic scale featuring Sylvac Direct RS-232 Output. Using a high accuracy capacitive sensor, **DIGI-MET PLUS** gages can be connected to any computer, data collector or printer without an interface.

Other features include:

- Large, high contrast LCD display.
- Freeze hold feature.
- Scale accuracy to DIN 862.
- Optoelectronic cable available for direct RS-232 output.
- PRESET function.
- Low drain lithium battery (2-3 yr life).
- ON/OFF feature.

SPECIFICATIONS:

- Resolution: .0005" (.01mm).
- Accuracy: .001" (.02mm).
- Repeatability: 1 digit
- Completely hardened throughout stainless steel construction.
- Direct inch/metric conversion.
- Measuring/tracking speed: 60"/sec.

MODEL NO. DESCRIPTION

| MODEL NO. | DESCRIPTION |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 19230 | Standard Measuring Range. 0-11½" Outside Measurement. 1 ¹³ / ₁₆ " to 13½" Inside Measurement. Kit Includes: Multi-Gage, pair of extension tips, pair of cone tips, pair of ¼" dia. gage balls, combination tapered/flat tips, floating locator pins, pointed groove measuring tips, durable molded case. |
| 19230-L | Extra-long Measuring Range. 0-23" Outside Measurement. 1 ¹³ / ₁₆ " to 25½" Inside Measurement. Kit Includes: Multi-Gage, pair of extension tips, pair of cone tips, pair of ¼" dia. gage balls, combination tapered/flat tips, floating locator pins, pointed groove measuring tips, durable molded case. |
| 19237 | Multi-Gage 2" Calibration Kit. Permits accurate pre-setting of Multi-Gage for hole-to-hole direct measurement and other applications. Comes with 2 floating locator pins. |

* Above ranges may vary nominally according to accessories used and applications.