

SAFETY DATA SHEET

Category

2B

1

Issue Date 2015-06-12

Revision Date 2018-09-20

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifiers

Product Name: Product Code: Facsimile Powder M-044-5066

Recommended Use of the substance or mixture and Restrictions on Use Industrial Use Only

Details of the Supplier of the Safety Data Sheet

Supplier Address Flexbar Machine Corporation 250 Gibbs Road Islandia, NY 11749 Website: www.flexbar.com E-mail: sales@flexbar.com

Emergency Telephone Numbers

Company Phone Number:

Emergency Telephone:

(610)-497-9000 (During Business Hours, 8:00am - 4:00pm EST) CHEMTREC: 1-800-424-9300 (Outside U.S. 1-703-527-3887)

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Hazard Class - Physical, Health, Environmental

Eye Damage/Irritation Skin Sensitizer

OSHA Defined Hazards

Combustible dust, may form combustible dust concentrations in air, explosion hazard

Label Elements - Pictograms, Signal Word, Hazard Statements, Precautionary Statements, & Supplemental Information



Warning

Hazards Statements		Precaution	Precautionary Statements - Prevention, Response, & Disposal	
H317	May cause an allergic skin reaction	P240	Ground/bond container and receiving equipment	
H320	Causes serious eye irritation	P261	Avoid breathing dust/fume/gas/mist/vapors/spray	
		P264	Wash hands and exposed skin thoroughly after handling	
		P272	Contaminated work clothing should not be allowed out of the workplace	
		P280	Wear protective gloves/protective clothing/eye protection/face protection	
		P321	Specific treatment (see on this label)	
		P363	Wash contaminated clothing before reuse	

P302+P352 P305+P351+ P338	IF ON SKIN: Wash with soap and water IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P501	Dispose of contents/container to an authorized disposal
	facility

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Cas No.	Weight-%	GHS Ratings
P(MMA/EA)	9010-88-2	50 — 60	Eye Damage/Irritation 2B (H320)
Calcium Carbonate	471-34-1	40 — 50	
Benzoyl Peroxide	94-36-0	0 — 1	Eye Damage/Irritation 2A (H319) Skin Sensitizer 1 (H317)

4. FIRST AID MEASURES

General Advice

Provide the SDS to medical personnel for treatment.

Inhalation:

Remove victim to fresh air. Seek immediate medical attention.

Eye Contact:

If product gets in the eyes, flush with lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.

Skin Contact:

Rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.

Clothing:

Remove contaminated clothing, wash thoroughly before reuse.

Ingestion:

If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Chemical (alcohol-resistant) foam, dry chemical, or carbon dioxide.

Unsuitable Extinguishing Media

Not known

Specific Hazards Arising from the Chemical

Polymers are combustible dusts; care should be taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures.

Special Fire Fighting Procedures:

Avoid extinguishing methods, which may generate dust clouds. Water stream can disperse dust into air producing a fire hazard and possible explosion hazard if exposed to ignition source. Firefighters should wear self-contained breathing apparatus.

Protective Equipment and Precautions for Firefighters

Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust. Polymers are sensitive to static discharge, follow grounding and bounding procedures. Polymers are not sensitive to mechanical impacts.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions

Before cleaning any spill or leak, individuals must wear appropriate Personal Protective Equipment that is specified in section 8. Keep airborne particulates at a minimum when cleaning up spills. Deny entry to all unprotected individuals. Remove any contaminated clothing and wash thoroughly before reuse.

Environmental Precautions

Extinguish all ignition sources. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

Methods and Material for Containment and Cleaning Up

Methods for Containment

Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material (e.g. sand or earth). May contaminate water supply.

Methods for Cleaning Up

Maximize ventilation (open doors and windows) and secure all sources of ignition. Use good, local ventilation with a minimum capture velocity of 100 ft/min (30 m/min) at point of product release. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Not a RCRA Hazardous waste.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling

Use in well ventilated areas. Avoid contact with skin, eyes and clothing. Avoid breathing dust. Use good personal hygiene and housekeeping. Avoid prolonged contact with the product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat. The temperature should remain at or under 72°F (22°C) at all times. Storing at above recommended temperature will cause product performance issues. Store in accordance with National Fire Protection Association recommendations. Observe all label precautions until the container is cleaned, reconditioned, or destroyed.

Incompatible Materials

Strong oxidizers, strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION					
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits		
P(MMA/EA) 9010-88-2					
Calcium Carbonate 471-34-1			NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)		
Benzoyl Peroxide 94-36-0	5 mg/m3 TWA	5 mg/m3 TWA	NIOSH: 5 mg/m3 TWA		

Engineering Controls

Use local explosion-proof ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

Personnel Protective Equipment (PPE)

Respiratory Protection

A respirator should be worn whenever workplace conditions warrant use of a respirator. If dust conditions are present, a N95 respirator dust mask is required. None required if airborne concentrations are maintained below any exposure limit that may be listed above. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134 or other appropriate governing standard.

Eye/Face Protection

Wear safety glasses, chemical goggles when splashing is possible, when dealing with this material. If necessary, refer to U.S. OSHA 29 CFR §1910.133, or other appropriate governing standard. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and Body Protection

Complete suit protecting against chemicals, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact: Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 480 min Splash contact: Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 120 min

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. An eyewash station and a safety shower are recommended. Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Wash hands thoroughly before eating, drinking, or smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Blue

Odor: Faint

Physical State: Solid Powder

Flash Point: 579 F,304 C

Flammable Limit (Air Volume %, 0% Lower / Upper)

Evaporation Rate No data available

Specific Gravity: 0

Auto ignition Temperature: 80°C

Boiling Range (low - high): N/A

10. STABILITY AND REACTIVITY

Material stability

Stable

Incompatible materials No data available

Hazardous decomposition products No data available

Possibility of hazardous reactions

Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Mixture Toxicity Component Toxicity

Routes of Exposure No data available

Target Organs Eyes Skin Respiratory System

Effects of Overexposure

Product Components Listed as Carcinogenic

CAS Number Description

None

<u>% Weight</u>

Carcinogen Rating No data available

12. ECOLOGICAL INFORMATION

Component Ecotoxicity

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Dispose waste material in accordance with Federal, State, and Local regulations. it is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste. Comply with all applicable federal, state and local regulations. Waste disposal options include land filling solids at permitted sites. Incinerate in a chemical incinerator equipped with an afterburner and scrubber. Use registered transporters.

Contaminated Packaging

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to

Hazard Class

residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with Federal, State and Local regulations

UN Number

Packing Group

14. TRANSPORT INFORMATION

Agency	Proper Shipping Name
DOT	Not Regulated, Polymer, NOS
ΙΑΤΑ	Not Regulated, Polymer, NOS
IMDG	Not Regulated, Polymer, NOS

15. REGULATORY INFORMATION

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

SARA 313

Benzoyl Peroxide 94-36-0

US State Right-to-Know Regulations

- None

Country

Date Prepared: 06/12/15

2015-06-12

Regulation **EINECS** SARA Hazard categories **TSCA** Inventory

All Components Listed No No Yes

Instability

16. OTHER INFORMATION

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)

Special



Reviewer Revision 1

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials on in any process, unless specified in the text.