




ROCKET ESPRESSO BOXER TIMER 1 GROUP 220V



WATER REQUIREMENTS

Height:	18.5 inches
Width:	19 inches
Depth:	19.5 inches
Weight:	102 lbs
Boiler Capacity:	8.3 L
Voltage:	208-240V
Wattage:	2300W
Amp Service Required:	20
Outlet Receptacle Requirements:	Nema L6-20R 

DISCLAIMER

Rocket Espresso USA recommends that you hire an espresso technician to install your machine. Claims made due to improper installation of the machine will not be supported under warranty.

WATER REQUIREMENTS

Dedicated cold-water access line with a standard female 3/8" compression fitting and a manual shut off valve (4 feet from the machine).

Water hardness should be tested before installation for proper filtration to be installed. There should be between 2-4 grains per gallon of hardness going into the machine. Repairs due to improper water filtration are not supported by warranty.

Minimum incoming water flow rate of 35 GPH and maximum line pressure of 70 PSI / 5 BAR

DRAIN REQUIREMENTS

The Rocket Espresso Boxer requires an open gravity drain beneath the machine. It's our recommendation that you drill a 2.5 inch hole directly beneath where you will place the machine. Please see the diagram for an example.

Please note, space is required beneath the counter of the espresso machine for drains, pipes, and filtration.

