



2-00 is the result of an innovative project that transforms the wheel balancing process, thanks to the perfect mix of speed, ease of use, strength and ergonomics. A professional product, so intuitive that it can be used by anyone.

WHAT IF EVERYTHING WERE THIS EASY?

PATENT PENDING



·LASER SPOTTER- Unique tool that allows selecting the correction planes with maximum accuracy and then precisely indicates the exact point of application of the weights

·LASER MATCHING- Laser line emitter which, together with the laser spotter, allows calculating the diameter of the rim

•OPB ONE PLANE BALANCING- Correction of both static and dynamic unbalance on one plane at once and with only one weight

•AUTOADAPTIVE MODE- The new tolerance calculation system

·LA SONAR for automatic measurement of the wheel width **CEMB PATENT**

•ALU-S BALANCING MODE- Adhesive weights on the internal rim planes with specific counterweight position indicator

•**LED LIGHT** to illuminate the working space inside the rim

•EMS SONAR (OPTION)- 1st Harmonic and Peak to Peak) Automatic and quick eccentricity measurement during the normal balancing cycle

•HUBMATCH- During the measuring cycle, the wheel's "maximum eccentricity point" is detected and displayed on the monitor, therefore allowing for its reduction during the re-mounting of the wheel on the vehicle (only with EMS Sonar)

•**TIRE SET-** The software indicates the best wheel positioning on the vehicle to get the best ride (conicity) and to minimize wheel vibrations (eccentricity) (option available only with EMS sonar)

•PNEUMATIC WHEEL LOCKING CEMB PATENT

Floor-to-floor time reduction/ Extremely easy and fast to use / Very accurate wheel centering

•AUTOMATIC POSITIONING AND LOCKING of the wheel in weight position

STANDARD ACCESSORIES PG. 42



ER75TD HubMatch®

A high volume RFV* diagnostic wheel balancer that uniquely uses advanced balancing features such as our Dynamic AutoAdaptive with OPB balancing and RFV* measurement combined with HubMatch®; a guided on car eccentricity cancellation process which significantly reduces floor-to-floor cycle time and provides an improved ride quality to eliminate the most difficult tire and wheel related vibration problems. All the best features from CEMB balancers; focused on performance, ease of use, efficiency and time savings. Pneumatic locking.

*Radial Force Vectoring

•Fast 5-second cycle time.

•AutoAdaptive, Dynamic OPB balancing software. •CEMB balancing software on a touchscreen automatically resolves residual static unbalance commonly left behind when dynamically balancing with traditional balancers causing hidden vibration complaints.

•An automatic laser spotter highlights the exact tape-on weight locations.

•Automatic LED lighting at the inside of the wheel greatly increases visibility.

•Automatic 3D direct weight placement

(distance, diameter and width measurements) are included standard. No manual key pad entry required to balance wheels.

•Electro-magnetic brake holds the wheel for more accurate weight placement.

•Automatic Approach system allows for faster floor to floor time.

•Made in Italy. Final assembly in USA. Power Supply: 220V, 1ph.

HUBMATCH[®] DIAGNOSTIC RFV WHEEL BALANCER



STANDARD ACCESSORIES PG. 42