Pro Series Digital Tire Inflator - "Compact" One Button Operation

Model #10962



100% Kink-Free Wire Sheathed Hose



- 0 Multi-Scale Gauge - psi, bar, & Kpa
- Wire Sheathed Hose Eliminates Hose Kinking 2
- Operation: Inflate, Deflate, & Measure Air Pressure 3
- 4 Includes: Air Chuck Style: Dual Angle (Hold-on)
- Large Digital LCD Screen Easy to Read Display
- Multi-Scale Gauge: PSI, kPa, Bar
- 2 x AAA Batteries
- 80 Hour Battery Life
- Great for use in workshops, service trucks, and hobbvists.
- Air Chuck Style: Dual Angle (Hold-on)
- Operation: Inflate, Deflate, Measure

Max. Inflation	174 psi <i>12 bar</i>
Scale	174 psi/ 12 bar/ 1200 Kpa/ 12kgF
Inlet Size	1/4" NPT
Hose Length	20 in. 500 mm
Weight	2 lbs. 0.8 kg
Accuracy	+/- 2 psi @25-75psi
Supply Pressure Max.	200 psi 13.79 bar

Automatic Handheld Tire Inflator - Rechargable & Portable

Model #10963







The Digital Tire Inflator is a innovative design that allows for 100% Portable Automotic Inflation/Deflation. As easy as just connecting the airline, setting desired air pressure, then let the automatic inflator do the rest.

Inflator has two programable "preset" for most commonly used pressures at the push of a button. The built OPS (Over Pressure Setting) is a great safety feature that allows for the technician to set the pressure and walk away; ideal for mobile service trucks that deal with truck, car, earthmover, and more

- Multi-Scale Gauge: PSI, bar, kPa, kgF
- Wire Sheathed Hose Eliminates Hose Kinking
- Operation: Inflate, Deflate, & Measure Air Pressure ß
- 4 Tough Poly Carbonate Construction - For Heavy Duty Use
- Includes Calibration Certification
- Large Backlift Digital Display
- **Tough Poly Carbonate Construction**
- Air Chuck Style: Single Straight (Clip-on)
- Supply Voltage: DC 12V Rechargable Battery (Li-ion)
- Wattage: 12W Maximum
- Battery Life: 15 Hours (fully charged continuous use)
- Includes: Inflator, Hose, Instruction Manual and AC Charger.

Scale	174 psi/ 12 bar/ 1200 Kpa/ 12kgF
Inlet Size	1/4" NPT
Hose Length	5 ft. <i>1.5 m</i>
Weight	4.5 lbs. 2 kg
Accuracy	+/- 0.3 psi @25-75psi
Supply Pressure Max.	182 psi <i>12.55 bar</i>

AVAILABLE ACCESSORIES:

Four-Way Manifold and (4) Hoses (6 ft. Hoses) & Inflation Unit

MODEL 10963-K

Inflate up to four tires at once all at the preset air pressure. Great for Mobile Service Fleets.

Four-Way Manifold and (4) Hoses (6 ft. Hoses) **ONLY**





MODEL 10963-K

Warning: Air pre-filters must be used with this inflator to ensure product accuracy & longevity





