5 Bar Tire Inflation Cage - Safety Inflation Cage

Model #90411



- 5-bar tire inflation cages are used for changing and inflating tires for trucks, buses, military vehicles, etc.
- Heavy duty tire inflation cages manufactured using steel that meets the toughest standards.
- These safety cages, a mandatory precaution for tire inflation, provide good protection and exceed the requirements of OSHA Standard 29 CFR 1910.177 in the U.S. Before using the portable inflation cage, please read the instructions carefully.

Dimensions (L x W x H)	Max. Tire Size	Weight
41" x 26" x 57"	54" OD x 20" W	183 lbs.
1041mm x 660mm x 1448mm	1371mm OD x 508mm W	83 kg.

OTR Tire Inflation Cage - Safety Inflation Cage

Model #90412



- OTR tire inflation cage is used to inflate tires for trucks, military vehicles, tractors and aircrafts.
- Strongest Tire Cage on the market. Built with 2" 51mm steel tubing 6% larger than the competitions' tubing – welded to a 3/16" 5mm steel base with added reinforcements.
- These safety cages, a mandatory precaution for tire inflation, provide good protection and exceed the requirements of OSHA Standard 29 CFR 1910.177 in the U.S. Before using the portable inflation cage, please read the instructions carefully.

Dimensions (L x W x H)	Max. Tire Size	Weight
41" x 39" 1/2" x 68"	62" OD x 33" W	293 lbs.
1041mm x 1003mm x1727mm	1574mm OD x 838mm W	133 kg.

Tire Inflation Cage Accessories

* DOES NOT FIT ALL MODELS. Contact ESCO representative for more details.

Inflation Cage Roller Kit*



The inflation cage roller kit is used to rotate the tires easily and without any effort directly into the inflation cage, giving you an easy access to the valve.


Automatic Tire Inflator Bracket




The automatic tire Inflator stand is used to support the tire Inflator directly on the inflation cage.

AUTOMATIC HD Tire Inflation Cage - 52" OD Safety Inflation Cage

Model #90422





- Equipped, on both of its doors, of a safety system that activates or deactivates the inflation of the tire. If one of the doors is open, the automatic tire Inflator will not be activated.
- You must close the 2 doors properly in order to inflate.
- HD inflation cage is equipped with an air hose and a power cable (110 Volt).

Dimensions (L x W x H)	Max. Tire Size	Weight
55 11/16" x 24" x 54"	52" OD x 19" W	578 lbs.
1422mm x 610mm x 1372mm	1287mm OD x 483mm W	263 kg.



MODEL 90422