

POWERMAX

PMMC SERIES

11 STEP AUTOMATIC SMART
CHARGER

PERFECT FOR CARS,
MOTORCYCLES, JET SKIS
AND MARINE APPLICATIONS



MODEL NUMBER	PMMC-04	PMMC-07
INPUT VOLTAGE	110-120 VAC, 50-60Hz	110-120 VAC, 50-60Hz
CHARGING CURRENT	2A (6V & 12V), 4A (12V)	3.6A (6V & 12V), 7.2A (12V)
AMBIENT TEMPERATURE <small>*OUTPUT POWER IS AUTOMATICALLY REDUCED WHEN TEMPERATURE IS GREATER THAN 40 C</small>	-4 F° to +122 F° (-20 C° to +50 C°)*	-4 F° to +122 F° (-20 C° to +50 C°)*
CHARGER TYPE	11 Step, Smart Charger	12 Step, Smart Charger
BATTERY VOLTAGE	6V & 12V	6V & 12V
BATTERY TYPE	Wet, Gel, MF, CA, EFB, AGM, LiFePO (4 Series)	Wet, Gel, MF, CA, EFB, AGM, LiFePO (4 Series)
HOUSING PROTECTION	IP65	IP65
DIMENSIONS (L x W x H)	7.09" x 3.15" x 1.96"	8.66" x 3.74" x 2.36"
WEIGHT	1.37 lbs	1.88 lbs
CERTIFICATION	ETL, FCC	ETL, FCC

BATTERY CHARGERS | MAINTAINERS | INVERTERS | GENERATORS
DC POWER SUPPLIES | CONVERTERS | POWER CENTERS
AUTOMATIC TRANSFER SWITCHES

(941) 201-8041
POWERMAXCONVERTERS.COM