



# F31T8/841/U



**Description** 31W 4100K T8 85 CRI Medium Bi-pin U-Bent 1 5/8 inch Spacer

**Ordering Code** 05289

**UNSPSC Code** 39101605

## Specifications

<b>Watts</b>	31
<b>Base Type</b>	G13
<b>Bulb Type</b>	T8
<b>MOL in/mm</b>	22.5/571
<b>Length</b>	2'
<b>MOD in/mm</b>	1.0/26
<b>Mercury Content (mg)</b>	7.5
<b>HG Form</b>	solid
<b>Approx Initial Lumens</b>	2750
<b>Approx Mean Lumens</b>	2475
<b>CT deg K</b>	4100
<b>CRI</b>	85
<b>Rated Life</b>	20,000
<b>Special Desc</b>	U-Bend 1-5/8 inch centers, Universal Start
<b>Approvals</b>	IMERC, TCLP Compliant

[watch](#) > [like](#) > [follow](#)



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 · (P) 1.800.852.2217 (F) 1.800.492.8975

Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 (F) 1.888.705.1335