

8127B

FT-One™ 3D Construction Belted Full Body Harness, Tongue Buckle Leg Adjustments

Features :

- Comfort Legs™ lateral leg strap construction greatly improves mobility and comfort
- New Modular Belt System™ allows for custom configuration of tool bag and pouch positions for ease of use, comfort, and efficiency
- ArrowGrip™ dorsal D-ring plate and new slip-resistant connectors minimize slippage for maximum comfort and minimal adjustment throughout the day
- Waist belt features four ANSI/ISEA 121-compliant tool tether anchor attachments, rated at five pounds each
- Industry-exclusive shoulder pad material is abrasion resistant to mitigate excess wear and keep the harness in service longer
- Advanced gel padding material disperses harness loads, eliminating hot spots and pressure points for all-day comfort
- Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance
- Includes fully adjustable suspension trauma relief system
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- FT-One™ Patent Pending
- Complies with ANSI Z359.11-2014



| Material Specifications | |
|------------------------------|--|
| Webbing | Polyester; 5,000 lb min. static strength |
| D-rings | Aluminum Alloy; 5,000 lb min. static strength |
| Buckles and Adjusters | Aluminum alloy and plated alloy steel; 3,372 lb min. static strength |

| Performance Specifications | |
|----------------------------|--------------------|
| Static Strength | 3,600 lb min. |
| ANSI User Capacity | 130 to 310 lb max. |
| OSHA User Capacity | 130 to 425 lb max. |

| Compliant With: | |
|-----------------|----------------------|
| OSHA | 1926.502 and 1910.66 |
| ANSI | Z359.11-2014 |

| Sizes & Part Numbers | | | | | | | |
|----------------------|----------------|-----------------|----------------|--------------|--------------|--------------|--|
| 8127BXS - XS | 8127BS - Small | 8127BM - Medium | 8127BL - Large | 8127BXL - XL | 8127B2X - 2X | 8127B3X - 3X | |

