

TECHNICAL DATA SHEET

OLD MASTERS® GEL STAIN

AVAILABLE SIZES: Half-pint (16), Pint (08), Quart (04) and Gallon (01)

PRODUCT CODES:	801 Natural	809 Fruitwood	818 American Walnut
	802 Golden Oak	810 Pickling White	819 Aged Oak
	803 Cherry	811 Dark Mahogany	820 Weathered Wood
	804 Red Mahogany	812 Maple	841 Crimson Fire
	805 Provincial	813 Cedar	842 Vintage Burgundy
	806 Early American	814 Spanish Oak	843 Rich Mahogany
	807 Dark Walnut	816 Natural Walnut	844 Espresso
	808 Special Walnut	817 Pecan	845 Carbon Black**

PRODUCT DESCRIPTION: Old Masters Gel Stain is a highly pigmented, oil-based stain designed to achieve intense colors on interior and exterior wood, fiberglass, primed metal and composition surfaces. Its thick formula allows easy application and superior color control, necessary to achieve a rich and uniform color on most surfaces in a single application. Ideal for difficult-to-stain woods such as pine, poplar, maple, plywood and veneers, as well as nonporous surfaces including metal, composition (Masonite), interior and exterior fiberglass doors and plastic moldings. Gel Stain comes in 24 factory-mixed colors and can also be intermixed or tinted to achieve custom colors.

SURFACE PREPARATION: All surfaces must be clean, dry and free from dirt, wax, grease, glue, and other contaminants or penetration and adhesion will be affected. Wood surfaces must be sanded smooth. Remove dust with a tack rag or a lint-free cloth dampened with mineral spirits. Surface defects should be repaired with an appropriate patching material.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION: Stain application varies based on surface material. Please see application instructions below.

Application on Bare Wood: Apply stain liberally with brush or soft rag and remove excess, wiping in the direction of the grain. For a darker color, re-stain when first coat is dry. For a lighter color, wipe with a rag dampened with paint thinner before stain has dried.

Application on Fiberglass & Composition Surfaces: Stain one section or panel at a time. Apply a liberal coat of Gel Stain with a firm synthetic brush or lint-free rag and work the stain across and into the grain uniformly, feathering out streaks while the stain is wet. Wipe brush often on a lint-free rag to remove excess stain.

Application over Painted Surfaces: To create a simulated wood look, apply stain to painted surface with foam or bristle brush or cheesecloth using long, smooth strokes. Realistic woodgrain patterns can be created by using the Old Masters Wood Graining Tool, as illustrated in the Old Masters Wood Graining Booklet.

Application over Previously Finished Surfaces: Scuff sand surface before application. Remove dust. Apply a liberal coat of Gel Stain with a firm synthetic brush or lint-free rag and work the stain across and into the grain uniformly, feathering out streaks while stain is wet. Wipe brush often on a lint-free rag to remove excess stain.

If applying stain exteriorly, topcoating with an exterior clear finish is strongly recommended.



OLD MASTERS® GEL STAIN

MIXING AND TINTING: Custom colors can be achieved by intermixing colors or by adding up to 10 ounces of universal or industrial colorant per gallon. The amount of colorant added may affect its performance and extend dry time. To lighten Gel Stain, mix any proportion with Natural Gel Stain. Stir for uniform consistency. **DO NOT THIN.**

COVERAGE: Approximately 1,000 to 1,200 square feet per gallon. If the wood is finely sanded or nonporous, coverage is approximately 800 to 1,600 square feet per gallon. If the surface is porous, coverage is approximately 300 to 500 square feet per gallon. Coverage will vary significantly depending on application method and condition of wood.

DRYING TIME: Approximately 6 to 8 hours depending upon temperature, humidity, air movement, and the amount of stain on the surface. For additional color depth, a second coat of stain can be applied after 8 hours. Ideal drying conditions recommended are 70° to 75°F and 35 to 50% humidity.

** Due to the nature and depth of color for the stain color Carbon Black, the minimum dry time is 24 hours. Dry time may also be extended due to excess stain application or lack of stain penetration.

CLEANUP: Using a cleaning solvent, such as paint thinner or mineral spirits is recommended for cleanup. The use of paint thinners or mineral spirits may violate VOC compliancy in your area. Check with your local government agencies to ensure proper compliancy.

To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.

FINISH COAT: We recommend Old Masters clear finishes. However, this stain can be top coated with most clears. If a lacquer topcoat is desired, test for compatibility before using. For exterior use, we suggest Old Masters Ascend Exterior® or Old Masters Spar-Marine Varnish. **When applying water-based finishes, allow a minimum of 24 hours before top coating.**

MAX VOC: 550 grams/liter (4.6 lbs/gal)

TECHNICAL DATA

SOLIDS BY WEIGHT: 36.3% to 48.8%

FLASH POINT: 102°F Tag Closed Cup

SOLIDS BY VOLUME: 29.5% to 29.8%

VISCOSITY AT 77 °: Thixotropic Gel

VOCs: 550 grams/liter

VEHICLE: Alkyd

THEORETICAL COVERAGE @ Mil DFT: 1200 sq. ft/gal

RECOMMENDED DFT PER COAT: Not Applicable

COVERAGE @ RECOMMENDED DFT: Not Applicable

WEIGHT PER GALLON: 7.22 to 8.97 LBS

AVERAGE DRY TIME @ 70°F AND 50% R.H.:

RECOMMENDED THINNER:

Approximately 6 to 8 hours

Do not thin. Used as packaged.

** Minimum 24 hours for Carbon Black

Limited Warranty Since Old Masters does not control the application of its products, nor is the condition of the surface to which they are applied, a Limited Warranty provided. If the products do not perform as specified, for whatever reason, Old Masters liability will under no circumstances exceed the replacement of the product.

Safety Data Sheets (SDS) are also available for this product.

Revised 02/2020



303 19th Street SE PO Box 286 Orange City, IA 51041
TF: (800) 747-3436 F: (712) 737-3893 myoldmasters.com