

Product Number	Dimension[mm]	T/R[%]	Wavelength[nm]
BP001	12.7	20:80±5%	400-700
BP002	12.7	30:70±5%	400-700
BP003	12.7	40:60±5%	400-700
BP004	12.7	60:40±5%	400-700
BP005	12.7	70:30±5%	400-700
BP006	12.7	80:20±5%	400-700
BP007	12.7	20:80±5%	650-900
BP008	12.7	30:70±5%	650-900
BP009	12.7	40:60±5%	650-900
BP010	12.7	60:40±5%	650-900
BP011	12.7	70:30±5%	650-900
BP012	12.7	80:20±5%	650-900
BP013	12.7	20:80±5%	900-1200
BP014	12.7	30:70±5%	900-1200
BP015	12.7	40:60±5%	900-1200
BP016	12.7	60:40±5%	900-1200
BP017	12.7	70:30±5%	900-1200
BP018	12.7	80:20±5%	900-1200
BP019	25.4	20:80±5%	400-700
BP020	25.4	30:70±5%	400-700
BP021	25.4	40:60±5%	400-700
BP022	25.4	60:40±5%	400-700
BP023	25.4	70:30±5%	400-700
BP024	25.4	80:20±5%	400-700
BP025	25.4	20:80±5%	650-900
BP026	25.4	30:70±5%	650-900
BP027	25.4	40:60±5%	650-900
BP028	25.4	60:40±5%	650-900
BP029	25.4	70:30±5%	650-900
BP030	25.4	80:20±5%	650-900
BP031	25.4	20:80±5%	900-1200
BP032	25.4	30:70±5%	900-1200
BP033	25.4	40:60±5%	900-1200
BP034	25.4	60:40±5%	900-1200
BP035	25.4	70:30±5%	900-1200
BP036	25.4	80:20±5%	900-1200
BP037	50.8	20:80±5%	400-700
BP038	50.8	30:70±5%	400-700
BP039	50.8	40:60±5%	400-700
BP040	50.8	60:40±5%	400-700
BP041	50.8	70:30±5%	400-700
BP042	50.8	80:20±5%	400-700
BP043	50.8	20:80±5%	650-900
BP044	50.8	30:70±5%	650-900
BP045	50.8	40:60±5%	650-900
BP046	50.8	60:40±5%	650-900
BP047	50.8	70:30±5%	650-900
BP048	50.8	80:20±5%	650-900
BP049	50.8	20:80±5%	900-1200
BP050	50.8	30:70±5%	900-1200
BP051	50.8	40:60±5%	900-1200
BP052	50.8	60:40±5%	900-1200
BP053	50.8	70:30±5%	900-1200
BP054	50.8	80:20±5%	900-1200
BP055	12.7*12.7	50/50±5%	400-700
BP056	12.7*12.7	50/50±5%	650-900
BP057	12.7*12.7	50/50±5%	900-1200
BP058	25.4*25.4	50/50±5%	400-700
BP059	25.4*25.4	50/50±5%	650-900
BP060	25.4*25.4	50/50±5%	900-1200
BP061	50.8*50.8	50/50±5%	400-700
BP062	50.8*50.8	50/50±5%	650-900
BP063	50.8*50.8	50/50±5%	900-1200
BP064	12.7	50:50±5%	400-700
BP065	12.7	50:50±5%	650-900
BP066	12.7	50:50±5%	900-1200
BP067	25.4	50:50±5%	400-700
BP068	25.4	50:50±5%	650-900
BP069	25.4	50:50±5%	900-1200
BP070	50.8	50:50±5%	400-700
BP071	50.8	50:50±5%	650-900
BP072	50.8	50:50±5%	900-1200