

 ICOM

IC-M85

VHF MARINE TRANSCEIVER

*A Marine and Land Mobile Radio  
Combined in One*



# Ultra Compact and Powerful with Land Mobile Features



[ Actual Size ]



## Compact and Lightweight

The IC-M85 is the most compact (W×H×D: 56 × 92 × 29 mm; 2.2 × 3.6 × 1.1 in) and lightweight (weight: 246 g; 8.7 oz (with BP-290, FA-SC58V and MBB-3)) commercial grade marine and land mobile hybrid radio in the world\*.

\* As of November 2017, researched by Icom.



## Covering 136–174 MHz Land Mobile Frequency

In addition to VHF marine channels, the IC-M85 covers 136–174 MHz land mobile channels. Up to 100 programmable channels are available for land mobile use. Each channel is programmable with CTCSS and DTCSS tone.



## 700 mW Powerful Audio

Despite its compact body, the IC-M85 delivers 700 mW of loud audio. Clear communications is vital in noisy environments.



## Private Conversation

The radio has a built-in Voice Scrambler and provides private communication between stations (32-code, compatible with UT-112 voice scrambler unit).

### Supplied accessories;



BP-290 battery pack



BC-227 rapid charger

VHF MARINE TRANSCEIVER  
**IC-M85**

# Marine Handheld



## Automated Emergency Alarm

The IC-M85 has three emergency related functions: the MOB Alarm, Man Down and Lone Worker functions. If one of these functions are activated, the radio automatically makes an emergency alarm.



## Instant Operation with Multi-Function Button

Channel group changing (marine ⇌ land mobile) or the scrambler function ON/OFF can be assigned in the multi-function button on the top panel\*. The Key lock function can be activated by holding the button.



\* Ask your dealer for details.



## IP67 and MIL-STD Rugged Construction

The IC-M85 is built durable to endure 1 m submersion for 30 minutes and dust-tight protection. The radio also passes MIL-STD-810 specifications.



### And More

- AquaQuake™ prevents audio degradation from a water-logged speaker
- Internal VOX capability for hands-free operation
- 14 hours of long battery life (TX: RX: Standby=5:5:90.)
- 5 W output power (land mobile channels for USA: 2 W)
- Weather channel receiving
- The self check function checks internal temperature, and connected battery voltage (over voltage detection)
- Monitor function □ Priority scan function
- Dual/Tri-watch function for monitoring CH16 and/or call channel
- Favorite channel function for quick access to often used channels

\* SA for USA plug. SE for Europe plug.



BC-123S\* AC adapter    FA-SC58V antenna    MBB-3 belt clip    Hand strap

## Variety of Audio Accessories

### Submersible Speaker-Microphones

<p><b>HM-236</b></p>	<p><b>HM-222</b> With 3.5 mm earphone jack.</p>
----------------------	---

### Hands-Free Operation with Headsets

	<p><b>HS-94</b> Earphone-headset</p>	<p>or</p> <p>+</p> <p>or</p>	<p><b>VS-5MC</b> PTT switch cable</p>
	<p><b>HS-95</b> Behind-the-head headset</p>		
	<p><b>HS-97</b> Throat microphone</p>		

### Earphones and Speaker Microphones for Noisy Environments

	<p><b>SP-27</b> Tube earphone*</p>	<p>or</p> <p>+</p> <p>or</p>	<p><b>AD-135</b> 3.5 mm earphone jack adapter.</p> <p>or</p> <p><b>HM-222</b> Waterproof speaker microphone with 3.5 mm earphone jack.</p>
	<p><b>SP-29</b> Earhook type earphone*</p>		
	<p><b>SP-40</b> Earphone*</p>		

\* With 3.5 mm plug.

### Stylish Operation with Tie-Clip Microphone and Earphones

	<p><b>SP-26</b> Tube earphone*</p>	<p>or</p> <p>+</p> <p>or</p>	<p><b>HM-163MC</b> Tie-clip microphone</p>
	<p><b>SP-28</b> Earhook type earphone*</p>		
	<p><b>EH-15B</b> Earphone*</p>		

\* With 2.5 mm plug.

### Covert Earphone

**SP-32**  
Tube earphone adapter for use with EH-15B and HM-163MC.

OPTIONS


**BATTERY PACK AND CASE**



**BP-290**  
Rechargeable Li-ion battery with intelligent reporting. 1910 mAh (min.) 2010 mAh (typ.). IP67 Waterproof

**BP-291**  
Battery case LR6 (AA) x 5. IP54 Water resistance

**MULTI-CHARGER**



**BC-214** **BC-157S** **AD-132N**

Charges up to six BP-290 batteries in 2.8 hours (approx.). AD-132N is supplied with BC-214, depending on version.


**CONNECTABLE TYPE CHARGER**



**BC-226** **BC-228**

Charges the BP-290 in 2.7 hours. (approx.) Connects up to six BC-226 units.

**INTELLIGENT CHARGER** **DESKTOP CHARGERS**



**BC-225** **BC-123S\***  
Shows the charging information with LED lighting. Charges the BP-290 in 2.5 hours. (approx.)

**BC-227** **BC-123S\***  
Charges the BP-290 in 2.7 hours. (approx.)

**BC-219N** **BC-123S\***  
Charges the BP-290 in 2.5 hours. (approx.)

\* SE for Europe plug. SUK for UK plug. SV for Australia plug.

**BELT CLIPS** **BELT HANGERS** **ACC ADAPTOR**



**MBB-3** **MB-136**  
Alligator type. Swivel type.

**MB-96N** **MB-96F** **MB-96FL**  
Swivel type. Fixed type. Long type.

**AD-118**  
14-pin multi-connector to 6-pin Hirose connector

**CARRYING CASES** **CIGARETTE LIGHTER CABLE & POWER SUPPLY CABLES** **ANTENNA**



**LC-187** **LC-188**  
Hard type. Hard type. Charging is possible while the case is attached.

**CP-23L** **OPC-515L** **OPC-656**  
For use with the BC-219N or BC-227. For use with the BC-219N, BC-225 or BC-227. For use with the BC-214.

**FA-SC58V**

SOFTWARE

• **RS-BC225** : Intelligent charger software for Windows® PC. For use with BC-225.

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. Windows is either a registered trademark or a trademark of Microsoft Corporation in the United States and/or other countries. All other trademarks are the properties of their respective holders.

**Icom Inc.** 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 [www.icom.co.jp/world](http://www.icom.co.jp/world)

Count on us!

**Icom America Inc.**  
12421 Willows Road NE,  
Kirkland, WA 98034, U.S.A.  
Phone: +1 (425) 454-8155  
Fax: +1 (425) 454-1509  
E-mail: [sales@icomamerica.com](mailto:sales@icomamerica.com)  
URL: <http://www.icomamerica.com>

**Icom (Europe) GmbH**  
Communication Equipment  
Auf der Krautweide 24  
65812 Bad Soden am Taunus, Germany  
Phone: +49 (6196) 76685-0  
Fax: +49 (6196) 76685-50  
E-mail: [info@icomeurope.com](mailto:info@icomeurope.com)  
URL: <http://www.icomeurope.com>

**Icom France s.a.s.**  
Zac de la Plaine,  
1 Rue Brindejonc des Moulinais, BP 45804,  
31505 Toulouse Cedex 5, France  
Phone: +33 (5) 61 36 03 03  
Fax: +33 (5) 61 36 03 00  
E-mail: [icom@icom-france.com](mailto:icom@icom-france.com)  
URL: <http://www.icom-france.com>

**Icom Canada**  
Glenwood Centre #150-6165  
Highway 17A, Delta, B.C.,  
V4K 5B8, Canada  
Phone: +1 (604) 952-4266  
Fax: +1 (604) 952-0090  
E-mail: [info@icomcanada.com](mailto:info@icomcanada.com)  
URL: <http://www.icomcanada.com>

**Icom Spain S.L.**  
Ctra. Rubi, No. 88 "Edificio Can Castanyer"  
Bajos A 08174, Sant Cugat del Valles,  
Barcelona, Spain  
Phone: +34 (93) 590 26 70  
Fax: +34 (93) 589 04 46  
E-mail: [icom@icomspain.com](mailto:icom@icomspain.com)  
URL: <http://www.icomspain.com>

**Icom (Australia) Pty. Ltd.**  
Unit 1 / 103 Garden Road,  
Clayton, VIC 3168 Australia  
Phone: +61 (03) 9549 7500  
Fax: +61 (03) 9549 7505  
E-mail: [sales@icom.net.au](mailto:sales@icom.net.au)  
URL: <http://www.icom.net.au>

**Icom Brazil**  
Rua Itororó, 444 Padre Eustáquio  
Belo Horizonte MG,  
CEP: 30720-450, Brazil  
Phone: +55 (31) 3582 8847  
Fax: +55 (31) 3582 8987  
E-mail: [sales@icombrasil.com](mailto:sales@icombrasil.com)

**Icom (UK) Ltd.**  
Blacksole House, Altira Park,  
Herne Bay, Kent, CT6 6GZ, U.K.  
Phone: +44 (0) 1227 741741  
Fax: +44 (0) 1227 741742  
E-mail: [info@icomuk.co.uk](mailto:info@icomuk.co.uk)  
URL: <http://www.icomuk.co.uk>

SPECIFICATIONS

		IC-M85	
GENERAL		Marine channels	Land mobile channels
Frequency coverage	Tx Rx	156.025–157.425 MHz 156.050–163.275 MHz	136.000–174.000 MHz
Usable channel groups, Number of channels		USA, INT, CAN, WX channels	100 land mobile channels
Type of emissions		16K0G3E	16K0F3E/11K0F3E
Channel spacing		25 kHz	25 kHz/12.5 kHz
Power supply requirement		7.2 V DC nominal	
Current drain (approximate)	Tx Rx	1.5 A (at 5 W)	0.9 A (at 2 W) 1.5 A (at 5 W)
Antenna impedance		50 Ω	
Operating temperature range		–20 °C to +60 °C; –4 °F to +140 °F	–30 °C to +60 °C; –22 °F to +140 °F
Dimensions (W×H×D) (Projections not included)		56 × 92 × 29 mm; 2.2 × 3.6 × 1.1 in (With BP-290)	
Weight (approximate)		246 g; 8.7 oz (with BP-290, FA-SC58V and MBB-3)	
TRANSMITTER			
Output power (at 7.2 V DC)	USA EXP	5/3/1 W	2/1 W 5/3/1 W
Max. frequency deviation		±5.0 kHz	±5.0 kHz (Wide) ±2.5 kHz (Narrow)
Frequency stability		±5.0 ppm	
Spurious emissions		–70 dBc typical	
FM hum and noise		40 dB	40 dB (Wide) 34 dB (Narrow)
Audio harmonic distortion		10% (at 60% deviation)	
Modulation limiting		60–100% of maximum deviation	
RECEIVER			
Sensitivity (at 12 dB SINAD)		0.25 μV typical	
Adjacent channel selectivity		70 dB typical	70 dB typical (Wide) 55 dB typical (Narrow)
Spurious response		70 dB typical	
Intermodulation		70 dB typical	
Audio output power	Internal SP External SP	700 mW typical (at 10% distortion with 12 Ω load)	700 mW typical (at 10% distortion with 8 Ω load)

Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810 G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I–C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard	
Dust & Water	IP67 (Dust-tight and waterproof protection)

**HiTechWireless**

Tel: 888.511.5162  
Fax: 866.341.3315  
[sales@hitechwireless.com](mailto:sales@hitechwireless.com)  
[HiTechWireless.com](http://www.HiTechWireless.com)