PNC380S PoC Device



The PNC380S is a compact, rugged, and easy-to-operate Push-to-Talk over Cellular (PoC) and Wi-Fi device. The PNC380S supports nationwide voice and video group calling, dispatching, and GPS location tracking It is AT&T Network Ready, has T-Mobile IoT Network Certification, PTCRB certified and features an optional dash-mount car kit.

Part Number

PNC380S

Standard

Specifications

Cellular Standards	FDD-LTE, WCDMA, GSM			
Built-in Wi-Fi	Built-in Wi-Fi 2.4GHz and 5GHz, 802.11 b/g/n			
Bluetooth	Bluetooth 4.2			
GPS	GPS/A-GPS			
Audio	Digital Noise suppression, high-volume speakers, 1W Rated Audio Power Output (Max 2W)			
Keypad	Full Keypad			
Display	2.0" 320×240 TFT Non-touch			
Camera	8MP Rear Facing			
Ruggedized	MIL-STD-810 G, IP67, ESD IEC 61000-4-2,			
Compliance	-40 to +140 F Operating Temperature			
Texting	Send, receive, and view text messages between dispatcher and other Hytera PoC devices			
Safety	Emergency button, Stun and Revive, Flashlight			
Battery	4000mAh Li-ion Polymer, ≥24h (5-5-90 working cycle)			
SIM	Nano SIM (8.8mm x 12.3mm)			
Ports	Micro USB 2.0, 3.5mm Audio, Dock Charger interface, Car Kit			
	Connection Contacts			
Memory	1GB RAM, 8GB ROM, Micro SD/TF card, up to 32GB			

Standard Accessories (Included with PNC380S)

2 Years

	,		
Part Number	Description		
PNC380S	PoC Device		
BP4006	Li-ion Battery		
PS2023	Switching Power Adapter		
PC80	USB Charging Cable		
RO03	Nylon Strap		
BC50	Belt Clip		
Warranty			

PNC380S PoC Device Accessories

Part #	Image	Technic	cal Specification	
BP4006 Li-Ion Polymer Battery	Troot Hysteld Control	Nominal Capacity: Battery Life 5/5/90: Nominal Voltage: Battery Life Cycle:	4000mAh 24h 3.85V 500 charges	
PS2023 Power Adapter (US)		Operating Voltage: Input: Output: Certification:	90–264VAC 100-120VAC 5VDC/2A UL	
PC80 Programming and Charging Cable		Connectors: Length: Connector Type:	USB to Micro USB 1 m USB to Micro USB	
MCL35-S Multi-unit Charger		Supported Battery Type: Charging Pockets: Input: Charging Current: Charger Type: Certification:	Li-ion and Li-polymer batteries 6 batteries and 6 devices 100-240VAC or 12VDC/7A 1400 mA (per pocket) Smart CE	
EAS07 Earpiece with in-line PTT & Transparent Acoustic Tube		VOX: PTT Key: Emergency Key: Connector Type: Speaker Power:	N/A Yes N/A 3.5mm plug 20mW rated; 30mW max	
EHS24 C-Style Earpiece with in-line Mic		VOX: PTT Key: Connector Type: Speaker Power:	N/A Yes 3.5mm Jack 5mW rated; 10mW max	
POA121 Wireless PTT and Charging Cable		For use with EHS24 Earpi Connection Distance: Certification: Working Time (5/5/90): Charging Time: IP Rating:	ece 8~10m CE, FCC, IC ≥100H <2H IP67	
RO03 Nylon Strap		Length: Material:	47.5cm Nylon	
BC50 Belt Clip		Applicable To Belts: Swivel: Material:	50mm or less No Polycarbonate	
EHS26R C-Style Earset for Right Ear		VOX: PTT Key: Connector Type: Speaker Power:	N/A Yes 3.5mm plug 10mW max	

PNC380S Car Kit and Vehicle Accessories

Part #	Image	Technica	al Specification	
CK10 Car Kit Body with Power Cable	POC RADIO OUTET PROCESS	enables the PNC380S to be	d vehicle mounting assembly that installed in a vehicle and allows emoved. The Car Kit also functions 174 x 79 x 54mm, weight is 225g 174 x 79 x 45mm, weight is 165g Docking chassis, locking bracket, locking bracket key On/Off Power Button External speakers, microphones, and push-to-talk buttons Polycarbonate 12VDC	
SM18A3 Palm Mic		VOX: PTT Key: Emergency Key: Connector Type: IP Rating:	N/A Yes N/A 10 Pin Connector IP54	
POA149 Visor Mic	Ó	Interface: Cable length:	3.5 mm jack 3.5m	
POA150 Wired PTT Button		Interface: Cable length:	3.5 mm jack 2m	
SM09S1 External Amplified Speaker	introduction of the control of the c	Connector Type: Speaker Power: IP Rating: Operating Temperature: -	10 Pin Connector 15W rated; 20W max IP55 30°C to 70°C	