Zoe Vision Espresso Machines







32

SHOT TIMER *

To accurately and reliably time coffee extraction



LED LIGHTING OF THE WORKING AREA

Effective work station no matter the light conditions.







EASY SERVICE


Fast access to the internal parts for quick and easy technical service

LOW SERVICE COST

Designed to decrease the maintenance and inspection costs



Characteristics



Through an electronic level probe the boiler is automatically filled and maintained to the right filling level.



ACTIVATED ELECTRONIC PRE-INFUSION

Management of the delayed activation of water solenoid in the first phase of brewing.



DOUBLE READING GAUGE

Allows to control at the same time the boiler pressure and the distribution pressure.



EASY SERVICE

Fast access to the internal parts for quick and easy technical service.



AUTOMATIC CLEANING CYCLE Process for coffee

groups cleaning.



LED LIGHTING OF THE WORK AREA* Allows efficient working in any condition of environmental lighting. (VISION only)



SHOT TIMER*

To accurately and reliably time coffee extraction. (VISION only)

Optional



AUTOSTEAM

Steam wand characterized by an electronic system that allows to mount and/or heat milk at the set temperature.



CUP WARMER

Dedicated resistor to keep all the cups at the optimal temperature.



EXTERNAL VOLUMETRIC



NAKED PORTAFILTERS





COMPLETE RANGE

Available versions VISION, SED, SED "Tall" and "Compact"



Version with shot timer and barista lights




Guarantees an electronic dosing system through the button panel




Versions








28.35 inches / 720 mm



37.40 inches / 950 mm



20.78 inches / 528 mm

1 group

VISION/SED

1 steam tap

1 water tap

1 one-cup portafilters

1 two-cup portafilters

2 group

VISION/SED

2 steam taps

1 water tap

1 one-cup portafilters

2 two-cup portafilters

3 group

VISION/SED


2 steam taps

1 water tap

1 one-cup portafilters

3 two-cup portafilters






2 group COMPACT

2 steam taps

1 water tap

1 one-cup portafilters

2 two-cup portafilters



TALL VERSION

1-2-3 group VISION SED

| _Technical data | | 1 group | 2 group | 3 group | compact |
|-----------------------|-------------|-------------------------|-----------|----------|----------|
| voltage | ٧ | 220-240 1N / 280-415 3N | | | |
| power imput | kW | 2.3 | 3.3 | 6 | 2.7 |
| steam boiler capacity | US gal / It | 1.19 / 4.5 | 2.64 / 10 | 3.7 / 14 | 1.85 / 7 |
| steam boiler power | kW | 2.15 | 2.95 | 5.6 | 2.5 |
| pump power | kW | 0.13 | 0.13 | 0.13 | 0.13 |
| net weight | lb / kg | 90 / 41 | 121 / 55 | 152 / 69 | 99 / 45 |


_Colors

| Black | RAL 9005 | |
|-------------------|---------------|--|
| White Black | RAL 9003 9005 | |
| White Matte black | RAL 9003 9005 | |
| White Red | RAL 9003 3002 | |

$C \in$

PERSONALISED GRAPHICS

Customization of internal panels with graphics and colors (on request).



For more information about our coffee machines please contact us at enquiries@sanremouk.com













HO: Unit 5 Mardle Way Business Park, Buckfastleigh, Devon TQ11 OJL S T 01364 644 445

LDN: Arch 4, Hackney Downs Studios, Amhurst Terrace, London E8 2BT T. +44 (0) 2030 959 741

www.sanremouk.com

www.sanremouk.com

