


ES 80

HIGH STRENGTH
CONTACT ADHESIVE



EVERSTRONG
ADHESIVE

CA COMPLIANT

CA Compliant

Long Open Time

Low Odor

SCAQMD Rule 1168 &
OTC Compliant

LEED Compliant

EverStrong™ Fast Tack
Bond Performance

Web Spray Pattern

EverStrong™ ES80 is a high strength contact adhesive with excellent performance characteristics. Applied on both surfaces to be adhered, ES80 is a high strength, high temperature contact adhesive providing strong permanent bonds for a wide variety of substrates to include decorative laminates and veneers, fiberglass, glass, upholstery, fabrics, foam, auto headliners, cork and particle board. As a single surface application, its high tack and repositionability make ES80 an ideal adhesive for quick temporary bonding. Formulated with extremely low VOCs to comply with CA and OTC states regulations.

PRODUCT USAGE

For strong permanent bonds, apply ES80 to both surfaces to be bonded. For repositionable temporary bonds, apply EverStrong™ ES80 evenly to one side of the substrates to be bonded. Spray an even coat of adhesive with at least 80% to 100% coverage. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher.

STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	.95 + .02
Shear Adhesion:	100psi >200°F
Spray Tip:	ES6501
Spray Pattern:	Web Spray
Flammability:	Flammable per ASTM E-681-04
VOC:	<80g/l, EPA Method 24, No ODS, No HAPS
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

PACKAGING

ES80-009C(R)	9 lbs Disposable Canister
ES80-027C(R)	27 lbs Disposable Canister
ES80-140C(R)	140 lbs Returnable Canister
ES80-270C(R)	270 lbs Returnable Canister

All available in Clear (C) or Red (R)

KEY FEATURES

- ★ CA Compliant
- ★ Long Open Time
- ★ Low Odor
- ★ SCAQMD Rule 1168 & OTC Compliant
- ★ LEED Compliant
 - LEED Schools EQ Credit 4.0
 - LEED Core & Shell EQ Credit 4.0
 - LEED ND & CI EQ Credit 4.1
 - LEED EB MR Credit 3.0
- ★ EverStrong™ Fast Tack Bond Performance
- ★ Web Spray Pattern



Disclaimer of Warranty: NewStar Adhesives Inc. expressly disclaims all warranties either expressed or implied, including but not limited to merchantability, fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost. This provision relates to all sales and cannot be modified.

Manufacturer: NewStar Adhesives Inc., gluepros@newstaradhesives.com, 855-497-0700

See MSDS Data Sheet for Proper Handling and Safety Information

ES80-2

