




Clamex P

Detachable connector



P-system configurator on our website

Advantages and properties


- **Small opening 6 mm**, differentiation to furniture standards
- **Stackable with pre-installed connectors**, advantages in packaging, transport and logistics
- **Short assembly time on site**, minimal installation cost

- **Versatility for all angles**, same system for all joining situations
- **Freedom of choice during assembly**, detachable or glued construction



Clamex P-14

For panels from 16 mm



Technical data

Size.....	64 × 27 × 9.7 mm
Cutter.....	Ø 100.4 × 7 × 22
Material of connector.....	fiberglass reinforced plastic
Material of lever.....	zinc die cast
Installation tolerance.....	longitudinal ± 1 mm

Tensile strength

MDF	~ 900 N or 200 lb
Particle board	~ 800 N or 180 lb
Beech	~ 1000 N or 220 lb

Clamex P-14

Part no.

Box of 80 pairs.....	145334
Box of 300 pairs.....	145346
Box of 1000 pairs.....	145356

Drill jig P-System **125344**











Accessories starting page 98



Clamex P-10

For panels from 12 mm



Technical data

Size..... 52 × 19 × 9.7 mm
 Cutter..... Ø 100.4 × 7 × 22
 Material of connector..... fiberglass reinforced plastic
 Material of lever..... zinc die cast
 Installation tolerance..... longitudinal ± 0.5 mm

Tensile strength

MDF	~ 600 N or 130 lb
Particle board	~ 600 N or 130 lb
Beech	~ 900 N or 200 lb

Clamex P-10

Part no.





Box of 80 pairs.....	145372
Box of 300 pairs.....	145373
Box of 1000 pairs.....	145374

Drill jig P-System **125344**

Accessories starting page 98

Clamex P-Medius 14/10

For center panels from 16 mm



Technical data

Size..... 64 × 13.5 × 9.7 mm
 52 × 7.5 × 9.7 mm
 Cutter..... Ø 100.4 × 7 × 22
 Material of connector..... fiberglass reinforced plastic
 Material of lever..... zinc die cast
 Installation tolerance..... longitudinal ± 1 mm

	Load (19 mm)	Tensile strength
MDF	~ 700 N or 150 lb	~ 800 N or 180 lb
Particle board	~ 500 N or 110 lb	~ 600 N or 130 lb
Beech	~ 2400 N or 530 lb	~ 900 N or 200 lb

Clamex P Medius 14/10

Part no.

Box of 80 pairs.....	145370
Box of 300 pairs.....	145371
Box of 1000 pairs.....	145357

Drill jig P-System **125344**

Accessories starting page 98



Bisco P

Aligning element suitable for the P-System groove

Advantages and properties

- Ideal addition to **Clamex P** and **Tenso P**, fits into the P-System grooves, **without requiring a different cutter**
- **Bisco P-14** is ideal for **dry-assembly before gluing a joint with Tenso P-14**
- **For aligning P-System grooves**, aligning function without glue



- **Surface structure allows use as a connecting element** when gluing workpieces with PVA glue

Applications of Bisco P

- Wall panels
- Furniture with large depth
- Gluing of workpieces

Bisco P-14

Aligning element suitable for Clamex P-14 and Tenso P-14



Technical data





Size Bisco P-14	65 × 27 × 7 mm
Size Bisco P-10	52 × 19 × 7 mm
Cutter	Ø 100.4 × 7 × 22
Material	plastic
Installation tolerance	longitudinal ± 2 mm
Tensile strength with adhesive	~ 400 N or 90 lb

Bisco P-14	Part no.
Box of 80 pieces.....	145301
Box of 300 pieces.....	145302
Box of 1000 pieces.....	145303

Bisco P-10	Part no.
Box of 80 pieces.....	145304
Box of 300 pieces.....	145305

Bisco P-10

Aligning element suitable for Clamex P-10





Furniture manufacturing / Cabinet making

Your advantages with Clamex P

Aesthetic solution











– Differentiation to furniture standards

Stackable with pre-installed connectors

– Advantages in packaging, transport and logistics

Short assembly time on site

– Minimal installation cost

- | | |
|---|---|
|  Detachable |  Fast installation |
|  Aesthetic |  Strong |
|  High clamping force |  Lateral tolerance |
|  Stackable |  Shallow cutting |
|  Versatile |  No twisting |

Applications

Cabinetry | shelves | wardrobes | trade show exhibits | kitchen furniture | TV furniture | etc.

Production process

1. P-groove with CNC

- Same profile groove for both workpieces
- Short process time
- Direct data transfer from CAD / CAM
- No additional dowels for alignment necessary

2. Storage



- Small storage volume when stacking despite installed connector
- Remove the connector for surface treatment – fast and easy
- Short reaction time for finishing of standard parts

3. Delivery in parts

- Small transport volume with pre-installed connectors due to stackability
- Smaller stock volume for the dealer
- Easy transport of the parts into the building

4. Assembly on site

- Shorter assembly time at the customer's due to the pre-installed connectors
- Easy to assemble for a lay person with an allen key
- No second person necessary
- No dowels for lining-up necessary
- Easy to take apart when moving





Clamex P – Applications

Furniture manufacturing / Interiors

Your advantages with Clamex P

Aesthetic solution

– Differentiation to furniture standards

Stackable with pre-installed connectors

– Advantages in packaging, transport and logistics

Short assembly time on site

– Minimal installation cost

- | | | | |
|--|---------------------|--|--------------------------------------|
| | Detachable | | Fast installation |
| | Aesthetic | | Strong and form-locking |
| | High clamping force | | Lateral tolerance in P-System groove |
| | Stackable | | Shallow cutting depth |
| | Versatile | | No twisting |

Applications

sideboards | shelves | wardrobes | display cases |
kitchen furniture | TV furniture | etc.



© Domino Möbel AG

Store fixture / Kitchen manufacturing

Your advantages with Clamex P

Stackable with pre-installed connectors

– Advantages in packaging, transport and logistics

Versatility for all angles

– Same system for all joining situations

Freedom of choice during assembly

– Detachable or glued construction

Short assembly time on site


– Minimal installation cost

- | | | | |
|--|---------------------|--|--------------------------------------|
| | Detachable | | Fast installation |
| | Aesthetic | | Strong and form-locking |
| | High clamping force | | Lateral tolerance in P-System groove |
| | Stackable | | Shallow cutting depth |
| | Versatile | | No twisting |

Applications

wall elements | furniture | trade show exhibits |
changing rooms | stools | etc.





Clamex P-14



Clamex P-14



Clamex P Medius 14/10



Clamex P-14



Clamex P-14



Clamex P Medius 14/10



Clamex P-14

