

Direct Plug-In USB Headsets



Order Code
JPL-502S-USB

Order Code
JPL-501S-USB

TECHNICAL DATA

Microphone:

Directional: Bi-directional
 Impedance: Max. 2.2KΩ 1KH(RL=2.2KΩ)
 Sensitivity: -43±3dB RL=2.2KΩ Vs=2.0V (DC)
 Frequency Range: 100-10000Hz
 Operating Temp: -25°C~+70°C
 Storage Temp: -40°C~+80°C

Speaker:

Impedance: 150Ω±15% at 0.1 V1000Hz
 Sound pressure: 129dB ± 3dB at 1000HZ
 Frequency range: FO ~20KHZ(±10dB)
 FO: 210Hz ± 20%
 Operating Temp: -25°C 50°C
 Storage Temp: -25°C 60°C



USB-A



CLOTHING CLIP



HEADSET BAG & HANGING HOOK



JPL-501S / 502S

Improved sound quality and a flexible microphone boom arm with **Surround Shield™** noise cancellation.

Overview

Features	Single or dual ear Left / right ear side compatible Surround Shield™ noise cancelling microphone Clear, crisp sound 'Put and stay' ratchet microphone boom arm Overhead, sure-fit fully adjustable headband Fitted with 50mm leatherette ear cushions for maximum all day comfort
What's included	Draw string headset storage bag, spare 55mm foam ear cushions, headset hanging hook, clothing clip and Quick Start Guide
Headset Weight	Mid-weight Headset, ~ 70g / ~106g
Connection	USB-A
Compatibility	Direct Plug-in
Certifications	CE, RoHS, REACH
Warranty	2 Years repair or replacement warranty
MOQ	Master Shipping Carton: 40
EAN:	JPL-501S-USB: 5060126957904, JPL-502S-USB: 5060126957928
SKU:	JPL-501S-USB: 575-264-003, JPL-502S-USB: 575-264-004

