SAFETY DATA SHEET ULTTIMA ACRYLIC TRAFFIC PAINT





SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Supplier: Harris Group of Companies

Wildey, St. Michael Barbados, BB14006 Tel: 246-429-4840

Product Code and

Name:

12/0620 - Ulttima Acrylic Traffic Paint

Manufacturer: Harris Group of Companies

Wildey, St. Michael, Barbados, BB14006

General Information: Technical Department Tel: (246) 429-4840

Harris Paints Barbados (2003)

Limited

E-Mail: technical@harrispaintsonline.com

Fax: (246) 436-9544

Product Use: Traffic Line Marking

Date of Preparation: February 15, 2021 Revision#: 2

SECTION 2: HAZARDOUS COMPOSITION OF INGRE			COMPOSITION % (Wt. /Gal.)			
INGREDIENTS NAMES				COMPOSITIO)N % (Wt. /Ga	1.)
Common Name	Chemical Name	CAS No.	White	Black	Blue	Yellow
Titanium Dioxide	Titanium Dioxide	13463-	7.102	0	0	1.495
		67-7				
Ammonia	Ammonia	7664-	2.74	2.74	2.74	2.74
		41-7				
Polypropylene glycol	Polypropylene	25322-	0.653-	0.653-	0.653-	0.687- 1.375
	glycol	69-4	1.306	1.306	1.306	
Texanol	Propanic acid,	25265-	1.31	1.31	1.31	1.38
	2,2,4-trimethyl-	77-4				
	1,3-pentanediol					
	monoisobutyrate					
Butyl cellosolve	2- Butoxyethanol	111-76-	<0.001	<0.001	<0.001	<0.001
		2				
Amorphous Silica	Quartz,	7631-	0.002-	0.002-	0.002-	0.002- 0.011
	Crystallized	86-9	0.011	0.011	0.011	
	Silicon dioxide					
Ethylene Glycol	1,2-ethanediol	107-21-	0.022	0.022	0.022	0.023
· ·		1				

SAFETY DATA SHEET

ULTTIMA ACRYLIC TRAFFIC PAINT





Phthalocyanate Blue	Copper	147-14-	0	0	2.2	0
	Phthalocyanine	8				
Carbon Black	Amorphous	1333-	0	2.3	0	0
	Carbon	86-4				

SECTION 3: HAZARDS IDENT	IFICATION			
Physical State and	Liquid (viscous)			
Appearance				
Emergency Overview	May aggravate medical conditions of eye, skin and respiratory system.			
Primary Routes of Exposure	Inhalation, Skin contact, Eye contact, Ingestion.			
Possible Effects to	Inhalation:-	Inhalation:- Irritation of respiratory tract. Prolonged inhalation		
Overexposure		may lead to mucous membrane irritation, dizziness and/or light-headedness, headache, nausea, coughing.		
Possible Effects to	Skin contact:-	Irritation of skin. Prolonged or repeated contact can		
Overexposure cont'd		cause dermatitis. Skin contact may result in dermal		
		absorption of component(s) of this product which		
	may cause headache, nausea, central nervous syste			
	depression.			
	Eye contact:-	Irritation of eyes. Prolonged or repeated contact may		
		cause conjunctivitis, tearing of eyes, and redness of		
		eyes.		
	Ingestion:-	Ingestion may cause dizziness and /or light		
		headedness, headache, vomiting, gastro-intestinal		
		disturbances, severe abdominal pain, apathy, central nervous system depression, respiratory problems,		
		intoxication, kidney damage, pulmonary edema, loss		
	of consciousness, acute poisoning, respiratory failur			
		cardiac failure, brain damage.		

SECTION 4	: FIRST-AID MEASURES
Skin	Flush skin with water. Then wash thoroughly with soap and water. If any product remains, gently
Contact:	rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeat applications may be needed.
	Remove contaminated clothing. Wash contaminated clothing before re-use. If irritation occurs,
	consult a physician.
Inhalation	Remove to fresh air. Restore and support continued breathing. Get emergency medical
	attention. Have trained person give oxygen if necessary. Get medical help for any breathing
	difficulty. Remove to fresh air if inhalation caused eye watering, headaches, dizziness or other
	discomfort. Get medical attention if discomfort or irritation persists.
Eye	Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If
Contact:	irritation or other effects persist, obtain medical treatment.

SAFETY DATA SHEET ULTTIMA ACRYLIC TRAFFIC PAINT





Ingestion: Flush out mouth. If swallowed, do not induce vomiting. If victim is conscious give at least 2

glasses of water. Obtain medical treatment immediately.

SECTION 5: FIRE-FIGHTING MEASURES					
Flammability of the product:	Non flammable				
Auto-Ignition Temperature:	None				
Flash Points:	None				
Fire Extinguishing Media:	Dry chemical or foam water fog. Carbon dioxide. In closed tanks, water or foam may cause frothing or eruption.				
Products of Combustion:	Carbon monoxide, carbon dioxide, monomer vapours, toxic gases. Propionaldehyde.				
Unusual Fire and Explosion Hazards:	Closed containers may explode when exposed to extreme heat or fire.				
Special Remarks on Fire	Water may be used to cool and protect exposed containers. Fire				
Hazards:	fighters should use full protective clothing, eye protection and self- contained breathing apparatus.				
	Vapours are heavier than air and may travel long distances to a source of ignition and flash back.				
Special Remarks on	Vapours can form explosive mixtures in air at elevated				
Explosion Hazards:	temperatures.				

SECTION 6: ACCIDENTAL RELEASE MEASURES				
General Measures:	Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Spills may be collected with absorbent materials. Evacuate all unnecessary personnel. Place collected material in an appropriate container. Complete personal protective equipment must be used during clean-up.			
Small Spills and Leaks:	Use absorbent material to pick up and dispose of properly.			
Large Spills and Leaks:	Shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessel. Use absorbent to collect excess residue. Keep salvageable material and rinse water out of sewers and water course.			

SECTION 7:	HANDLING AND STORAGE
Handling:	Store at a cool, constant temperature. Keep away from heat, sparks and open
	flames Minimum: 1°C Maximum: 40°C.
Storage cont	ainers: Polypropylene pails or lacquer lined tins.

SAFETY DATA SHEET ULTTIMA ACRYLIC TRAFFIC PAINT





Other Precautions:

Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes and breathing of vapours. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or sanding painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under Exposure Control/Personal Protection. Empty containers may contain residues.

SECTION 8: EXPOSURE CO	NTROLS / PE	RSONAL PROTEC	TION		
Common Name		CAS No.	ACGIH-TLV	OSHA-PEL	
			8-Hour TWA	8-Hour TWA	
Texanol		25265-77-4	Not est.	Not est.	
Titanium Dioxide		13463-67-7	10 mg/m ³	10 mg/m ³	
Amorphous Silica		7631-86-9	10 mg/m ³	6 mg/m ³	
Ammonia		7664-41-7	25 ppm	25 ppm	
Ethylene Glycol		107-21-1	Not est.	80 mg/m ³	
Butyl Cellosolve		111-76-2	20 ppm	240 mg/m ³	
Polypropylene glycol		25265-77-4	Not est.	Not est.	
Amorphous Carbon		1333-86-4	3.5mg/m ³	3.5mg/m ³	
Copper Phthalocyanine		147-14-8	10 mg/m ³	Not Listed	
Personal Protection					
SI	kin	Impervious clo	J	o eliminate possible skir	
н	ands	Impervious gloves such as neoprene or nitrile rubber gloves should be worn.			
R	espiratory	ventilation to reduce vapours build up. Use of an appropriate NIOSH/MSHA approved or equival positive pressure sealing surface face piece respirator outfit with organic vapour cartridges and paint spray (Dust / N prefilters.			
Ey	/es		or glasses recommende ield could be used to pro	ed especially for overhead otect facial skin also.	

N.B.: Keep running water sources on site in cases of emergency and for after work cleaning.

SAFETY DATA SHEET

ULTTIMA ACRYLIC TRAFFIC PAINT





SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES					
Physical State and Appearance:	Liquid	Odour:	Moderate		
pH:	9- 10	Colour:	White, yellow, blue, black		
Soluble / Insoluble:	Soluble in water	Viscosity:	75-80 K.U.		
Melting / Freezing Point:	Not available	Solubility:	Not available		
Boiling / Condensation Point:	100 – 260.5° C	Critical	Not available		
		Temperatures:			
Specific Gravity:	Not available	Volatility:	Not available		
Vapour Density:	Not available	Vapour Pressure:	Not available		
Evaporation Rate:	Not available				

3,4 - Third and fourth listed bases

Stability and reactivity: This product is stable under normal conditions. See Section 5 Fire Fighting

Measures.

Conditions to avoid: Elevated temperatures, contact with oxidising agents, sparks, freezing, open

flame, extremes in temperature.

Materials to avoid: Oxidisers, acids, nitric acid, hydrofluoric acid.

SECTION 11: TOXICOLOGICAL INFORMATION

Supplemental Health No additional effects are anticipated besides those mentioned in Section 5 Fire

Information: Fighting Measures.

This product has not been listed by IARC, OSHA, ACGIH, DSL, TSCA but contains

ingredients which are toxic by ingestion, inhalation and through the skin.

Carcinogenicity Titanium dioxide has been listed by the IARC as a possible carcinogen to

humans based on inadequate evidence in humans and sufficient evidence of

carcinogenicity in experimental animals.

SECTION 12: ECOLOGICAL INFORMATION

There is no data available on the product.

General Note: Do not allow undiluted product or large quantities of products to reach ground

water, water courses or sewage systems.

SECTION 13: DISPOSAL CONSIDERATION

Dispose of in accordance with all applicable regulations ensuring no

contamination of surrounding environment.

SAFETY DATA SHEET

ULTTIMA ACRYLIC TRAFFIC PAINT





SECTION 14: TRANSPORTATION INFORMATION

UN ID No.: This product is not controlled or regulated under DOT, IATA.

DOT: Classification: Paint "protect from freezing" IATA: Classification: Paint "protect from freezing"

SECTION 15: REGULATORY INFORMATION

Products As of the date of this SDS, this product was not being regulated or controlled.

Product Components: Texanol – 246-77-9, Titanium dioxide – 236-675-5, Amorphous silica – 231-545-

EINECS No.: 4, Ammonia – 231-635-3, Ethylene gylcol – 203-473-3, Butyl cellosolve – 203-905-

0, Polypropylene glycol - 200-338-0, Carbon Black - 215-609-9, Copper

Phthalocyanine 205-685-1

DSCL (EEC): Amorphous silica Xn, Xi, R20

Ammonia R10, R23, R24, R34, R50

Butyl cellosolve Xn, R20, R21, R22, R36, R38

Ethylene gGlycol Xn, R22 Polypropylene R20, R22

glycol

Titanium Dioxide Not listed
Texanol Not listed
Amorphous Not listed

Carbon

Copper Xi, R36, R38

Phthalocyanine

IARC: Titanium dioxide Group 2B – Possible carcinogen to humans

Amorphous Group 2B – Possible carcinogen to humans

Carbon

Texanol Not listed
Amorphous silica Not listed
Ethylene glycol Not listed
Butyl cellosolve Not listed
Ammonia Not listed
Polyproplyene Not listed

glycol

SARA Title III

Section 311/312: Titanium dioxide Immediate (Acute) Health and Delayed (Chronic) Health

Hazard

SAFETY DATA SHEET

ULTTIMA ACRYLIC TRAFFIC PAINT





	Ethylene glycol Amorphous silica Polypropylene glycol Butyl cellosolve Texanol Amorphous Carbon Copper Phthalocyanine	Immediate (Acute) Health and Delayed (Chronic) Health Hazards, Fire, Sudden Release of Pressure and Reactive Hazards Not listed
Section 313:	Ethylene glycol Ammonia Copper Phthalocyanine Titanium dioxide Amorphous silica Polypropylene glycol Butyl cellosolve Texanol Amorphous Carbon	Listed Listed Listed Not listed
WHMIS:	Ethylene glycol Ammonia Butyl cellosolve Amorphous Carbon Titanium dioxide Amorphous silica Polypropylene glycol Texanol	Class D, Div 1, Subdiv B: Material causing immediate and serious toxic effects (TOXIC), Class D, Div 2 Subdiv A: Material causing other effects (TOXIC). Class A: Compressed gas, Class B, Div 1: Flammable and combustible material. Class D, Div 1, Subdiv A: Material causing immediate and serious toxic effects (VERY TOXIC), Class E: Corrosive Class B, Div 3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F). Class D, Div 2, Subdiv A: Poisonous and infectious material - Other effects - Very toxic.Class D Div 2, Subdiv B - Poisonous and infectious material - Other effects - Toxic Not listed Not listed Not listed

SAFETY DATA SHEET

ULTTIMA ACRYLIC TRAFFIC PAINT





	Copper Phthalocyanine	Not listed	
DSCL:	Ethylene glycol Texanol Titanium dioxide Amorphous silica Polypropylene glycol Butyl cellosolve Amorphous Carbon Copper Phthalocyanine	R22, S46 Not listed S26, S28A, S37, S39, S45	
TSCA:	Ethylene glycol Titanium dioxide Texanol Ammonia Amorphous silica Polypropylene glycol Butyl cellosolve Amorphous Carbon Copper Phthalocyanine	Not listed	
ATSDR:	Ammonia	Inhalation :- Acute Chronic Oral :-	1.7 ppm 0.1 ppm 0.3 mg/kg/day
	Ethylene Glycol	Inhalation :- Acute Oral :- Acute	2mg/m ³ 0.8 mg/kg/day
	Butyl Cellosolve Titanium dioxide Texanol Amorphous silica Polypropylene glycol Amorphous Carbon	Inhalation :- Acute Chronic Not listed Not listed Not listed Not listed	6ppm 0.2ppm

SAFETY DATA SHEET

ULTTIMA ACRYLIC TRAFFIC PAINT





Copper Not listed Phthalocyanine

SECTION 16: OTHER INFORMATION

Risk Phrases used in Section 15 above

R10: Flammable

R20: Harmful by inhalation

R21: Harmful if in contact with skin

R22: Harmful if swallowed.

R23: Toxic by inhalation

R24: Toxic in contact with skin

R34: Causes burns

R36: Irritating to eyes

R38: Irritating to skin

R50: Very toxic to aquatic organisms

Safety Phrases used in Section 15 above

S 26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 28A: After contact with skin, wash immediately with plenty of water.

S 37: Wear suitable gloves.

S 37/39: Wear suitable gloves and eye/face protection.

S 45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information contained herein is based on data available at the time of preparation of this data sheet and which is believed to be reliable. However, it is the users' responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This information is given in good faith, but no warranty, expressed or implied is made.

This SDS complies with general SDS requirements for Canada, the USA and the European Union and fulfils the ISO standards for format and content.