

# SAFETY DATA SHEET

## EXCEL FLAT EMULSION



### SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Supplier:	Harris Group of Companies Willey, St. Michael Barbados, BB14006 Tel: 246-429-4840
Product Code and Name:	12/2850 – Excel Flat Emulsion White
Manufacturer:	Harris Group of Companies Willey, St. Michael, Barbados, BB14006
General Information:	Technical Department Harris Paints Barbados (2003) Limited Tel: (246) 429-4840 Fax: (246) 436-9544 E-Mail: technical@harrispaintsonline.com
Product Use:	Interior/Exterior Paint
Date of Preparation:	September 6 <sup>th</sup> , 2017 Revision#: 0

### SECTION 2: HAZARDOUS IDENTIFICATION

GHS Classification	Classification Categories
Flammable Liquid	Category 4:
Acute Toxicity	
Oral	Category 5
Dermal	Category 5
Inhalation: Gas	Not Applicable
Inhalation: Vapour	Category 5
Inhalation: Dust and Mist	Not classifiable under normal handling
Skin corrosion/Irritation	Category 3: Irritant
Eye damage/ Eye irritation	Category 2B
Respiratory Sensitisation Solid/Liquid	No available data
Respiratory Sensitisation Gas	Not classifiable
Skin Sensitisation	No available data
Germ Cell Mutagenicity	Not available data
Carcinogenicity	No available data
Reproductive toxicity	No available data
Effects on or via lactation	Not classifiable
Specific Target Organ/Systemic Toxicity (Single Exposure)	Not classifiable for skin or inhalation. No available data for ingestion
Specific Target/Systemic Toxicity (Repeated Exposure)	No available data

# SAFETY DATA SHEET

## EXCEL FLAT EMULSION



Aspiration Hazard	No available data
Hazard to the Aquatic Environment (Acute)	No available data
Hazard to the Aquatic Environment (Chronic)	No available data

### Hazard Statement

Combustible liquid

May be harmful if swallowed

May be harmful in contact with skin for prolonged or repeat periods

May be harmful if swallowed and enters airways

May be harmful with prolonged or repeat inhalation

Cause mild skin irritation to compromised skin

Cause eye irritation

May cause damage to skin, eyes, respiratory tract, lungs, liver and CNS through prolonged or repeated exposure due to inappropriate use

Harmful to aquatic life

### Symbols



### Signal word

**Danger**

### Precautionary Statement

May be harmful in contact with skin, inhalation, or ingestion.

Keep out of reach of children

1. Keep away from heat, open flames, and hot surfaces. No smoking
2. Do not eat or drink when using this product.
3. Wear protective gloves, eye/face protection and long-sleeved clothing to avoid skin contact.
4. Avoid breathing dust, mist, or spray.
5. Use in a well-ventilated area.
6. Wash hands with soap and water thoroughly after handling.
7. Avoid release to the environment.

### SECTION 3: HAZARDOUS COMPOSITION OF INGREDIENTS AND INFORMATION

INGREDIENTS NAMES			COMPOSITION % (Wt./Gal.)
Common Name	Chemical Name	CAS No.	White
Microbiocide	N/A Microbiocides Mixture	Mixture	0.6185
Titanium Dioxide	Titanium Dioxide	13463-67-7	6.857
Tetrapotassium pyrophosphate	Diphosphoric acid, potassium salt	7320-34-5	0.0291
Ethylene glycol	1,2-ethanediol	107-21-1	0.7037
Propylene glycol	1,2-Propylene glycol	57-55-6	< 0.01

# SAFETY DATA SHEET

## EXCEL FLAT EMULSION



Triton X-100	<i>t</i> -Octylphenoxypolyethoxyethanol	9002-93-1	0.0393
Talc	Magnesium silicate	14807-96-6	1.691 – 2.819
Quartz, Silica	Quartz, Crystallised Silicon Dioxide	14808-60-7	< 0.03

### SECTION 4: FIRST-AID MEASURES

<b>Skin Contact:</b>	If on skin, wash with plenty of water and soap. Take off contaminated clothing and wash before re-use. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeat applications may be needed. If skin irritation or rash occurs, get medical attention.
<b>Inhalation:</b>	Remove person to fresh air and keep comfortable for breathing. Have trained person give oxygen if necessary. If necessary, restore and support continued breathing and get emergency medical attention. Get medical help for any breathing difficulty. Remove to fresh air if inhalation caused eye watering, headaches, dizziness, or other discomfort. Get medical attention if discomfort or irritation persists.
<b>Eye Contact:</b>	Immediately flush cautiously with large amounts of water, especially under lids for at least 15 minutes. Remove contacts lenses, if present and easy to do so and continue rinsing. If irritation or other effects persist, obtain medical treatment.
<b>Ingestion:</b>	Rinse mouth. If swallowed, do not induce vomiting. If victim is conscious give at least 2 glasses of water. Obtain medical treatment immediately if feeling unwell.

### SECTION 5: FIRE-FIGHTING MEASURES

In case of fire use and be aware of the following:

<b>Suitable Extinguishing Media:</b>	Dry chemical, foam or carbon dioxide. Water should only be used to cool fire-exposed containers, structures and to protect personnel or to dilute and flush away from sources of ignition.
<b>Unusual Fire and Explosion Hazards:</b>	Closed containers may explode when exposed to extreme heat or fire. Vapours may concentrate in confined areas. Vapours may be heavier than air and may travel along distances to a source of ignition and flash back.
<b>Fire Fighting Procedure:</b>	Wear full protective clothing such as heat insulating clothes and gloves, eye and face protection and respiratory protection. Self-contained breathing apparatus should be used when entering the hot zone. Remove any combustible material from the surrounding area where safe to do so. Start firefighting from an up wind/wind ward direction.

# SAFETY DATA SHEET

## EXCEL FLAT EMULSION



Only use the specified extinguishing media.  
Dike and collect water used to fight fire.

**Products of Combustion:** Carbon monoxide and other unidentified components.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>General Measures:</b>	<p>Comply with all applicable health and environmental regulations.</p> <p>Evacuate all unnecessary personnel upwind/windward.</p> <p>Eliminate all sources of ignition such as heat, sparks, open flames and other combustible materials.</p> <p>Cordon area from accidental entry.</p> <p>Complete personal protective equipment must be worn during clean-up.</p> <p>Contain and recover liquid when possible.</p>
<b>Small Spills and Leaks:</b>	<p>Use non-combustible, absorbent material such as dry sand, vermiculite and earth and place into containers to dispose of properly. Do not flush to sewer systems.</p>
<b>Large Spills and Leaks:</b>	<p>Shut off leak if safe to do so.</p> <p>Dike and contain spill far ahead of liquid for later disposal.</p> <p>Pump to storage or salvage vessel (if quantity allows).</p> <p>Use absorbent material to collect excess residue.</p> <p>Keep salvageable material and rinse water away from sewers and water courses.</p>

### SECTION 7: HANDLING AND STORAGE

<b>General Precautions:</b>	<p>Do not use this product other than for the purpose specified by the manufacturer or Supplier.</p> <p>Keep out of reach of children.</p> <p>Do not expose such containers to heat, sparks, flame or other sources of ignition.</p> <p><b>NB.: Keep running water sources on site in cases of emergency and for after work cleaning.</b></p>
<b>Handling:</b>	<p>Use only with adequate ventilation.</p> <p>Do not take internally.</p> <p>Avoid contact with skin and eyes and breathing of vapours.</p> <p>Wash hands thoroughly after handling, especially before eating or smoking.</p> <p>Avoid conditions which result in formation of inhalable particles such as spraying or sanding painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under Section 8 below.</p>
<b>Storage:</b>	<p>Smaller quantities should be stored in polypropylene pails or lacquer lined tins if removing from the original containers from manufacturer or supplier.</p> <p>Keep containers tightly closed and upright when not in use.</p>

# SAFETY DATA SHEET

## EXCEL FLAT EMULSION



Empty containers may contain residues.  
Store in a well-ventilated place. Keep cool.  
Storage and use areas should be "No Smoking" areas.

### SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Common Name	CAS No.	EINECS	ACGIH-TLV 8-Hour TWA	OSHA-PEL 8-Hour TWA
Microbiocide	Mixture	Mixture	Not est.	Not est.
Titanium Dioxide	13463-67-7	236-675-5	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Tetrapotassium pyrophosphate	7320-34-5	230-785-7	Not est.	15 mg/m <sup>3</sup> respirable
Ethylene glycol	107-21-1	203-473-3	50 ppm	50 ppm
Propylene glycol	57-55-6	200-338-0	Not est.	Not est.
Triton X-100	9002-93-1	N/A	Not est.	Not est.
Talc	14807-96-6	206-961-5	2 mg/m <sup>3</sup>	Not est.
Quartz, Silica	14808-60-7	231-545-4	0.025 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>

#### Personal Protection Equipment

#### Skin

Impervious clothing should be worn to eliminate possible skin contact and irritation. Such as chemical resistant coveralls or neoprene apron if appropriate.

#### Respiratory

Impervious gloves such as rubber, or nitrile, gloves should be worn.  
Use in a well-ventilated area or provide local exhaust or ventilation to reduce vapours build up.  
Use of an appropriate NIOSH/MSHA approved face piece respirator outfitted with organic vapour cartridges and Dust / Mist prefilters when working for prolonged period in not well-ventilated areas.  
Warning: - Air-purifying respirators do not protect worker in oxygen deficient atmospheres.

#### Eyes

Chemical resistant safety goggles or glasses recommended especially for overhead work. Wear face shield to protect facial skin also. Maintain eyewash and quick drenching facilities in the work area.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance:	Liquid	Odour:	Slight
pH:	8.3 – 8.9	Colour:	White
Soluble / Insoluble:	Soluble in water	Viscosity:	87 KU
Melting / Freezing Point:	Not established	Solubility:	Soluble
Boiling / Condensation Point:	Not established	Autoignition Temperatures:	Not established

# SAFETY DATA SHEET

## EXCEL FLAT EMULSION



Specific Gravity:	1.05 – 1.27	Flash Point:	Not established
Vapour Density:	Not established	Vapour Pressure:	Not established
Evaporation Rate:	Not established		

### SECTION 10: STABILITY AND REACTIVITY

Stability and reactivity:	This product is stable under normal conditions. See Section 5 Fire Fighting Measures.
Conditions to avoid:	Elevated temperatures, contact with sparks, open flame, extremes in temperature.
Materials to avoid:	Strong oxidising agents and acids.

### SECTION 11: TOXICOLOGICAL INFORMATION

Possible Effects to Overexposure	<b>Inhalation:-</b>	Irritation of respiratory tract. Prolonged inhalation may lead to mucous membrane irritation, dizziness and/or light-headedness, headache, nausea, coughing, sneezing, central nervous system depression, kidney and liver damage.
	<b>Skin contact:-</b>	Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting. Possible sensitization to skin. Skin contact may result in dermal absorption of component(s) of this product which may cause headache, nausea, central nervous system depression.
	<b>Eye contact:-</b>	Irritation of eyes. Prolonged or repeated contact may cause conjunctivitis, tearing of eyes and redness of eyes.
	<b>Ingestion:-</b>	Ingestion may cause dizziness and/or light headedness, headache, vomiting, gastro-intestinal disturbances, severe abdominal pain, apathy, central nervous system depression, respiratory problems, intoxication, pulmonary edema, loss of consciousness.
Supplemental Health Information:	Persons with pre-existing skin disorders or eye problems or impaired liver, kidney, blood or respiratory function may be more susceptible to the effects of the substance. This product has not been listed by IARC, OSHA, ACGIH, DSL, TSCA but contains ingredients which are toxic by ingestion, inhalation and through the skin. Chemicals in their non-reportable form could be encountered when stripping or release of by-products may build-up in the headspace of the containers.	
Carcinogenicity	Microbiocides are listed as suspected of causing cancer under EEC. IARC has classified Quartz in its respirable form. Titanium dioxide has been listed by the IARC as a possible carcinogen to humans and sufficient evidence of carcinogenicity in experimental animals. However, no significant exposure is thought to occur as it is bound to other materials in the paint product.	

# SAFETY DATA SHEET

## EXCEL FLAT EMULSION



### SECTION 12: ECOLOGICAL INFORMATION

#### General Note:

There is no data available on the products but contains an ingredient known to be very toxic to aquatic life and with possible long-lasting effects.

Do not allow undiluted product or large quantities of products to reach ground water, water courses or sewage systems. It contains Triton X-100 that is not readily biodegradable.

Talc: 96 Hr LC50 Brachydanio rerio: >100 g/L [semi-static]

Titanium Dioxide: LC50 Pimephales promelas (fathead minnow) 96 h > 1,000 mg/l.

EC50 Pseudokirchneriella subcapitata (green algae) 72 h 61 mg/l. EC50 Daphnia magna (Water flea) 48 h > 1,000 mg/l

Propylene glycol: 24 hours LC50 Goldfish >5000 mg/l 48 h LC50 Guppy >10000 mg/l, 48 h EC50 Water flea >10000 mg/l.

Triton X-100: EC50 Daphnia 48 h 26mg/l. LC50 Pimephales promelas (fathead minnow) 96 h 8.9 mg/l

### SECTION 13: DISPOSAL CONSIDERATION

Dispose of material in accordance with all applicable regulations ensuring no contamination of surrounding environment.

### SECTION 14: TRANSPORTATION INFORMATION

This product is to be shipped as consumer commodity packaging, but it is the responsibility of the shipper to ensure full compliance with the applicable regulations. This product is not controlled or regulated under DOT, IATA.

UN ID No.: Not regulated

DOT: Classification: Not regulated

IATA: Classification: Not regulated

### SECTION 15: REGULATORY INFORMATION

**Products** As of the date of this SDS, this product was not being regulated or controlled. It also contains hazardous ingredients below the required reportable limits.

#### Product

#### Components:

DSCL (EEC):	Propylene glycol	Listed
	Ethylene glycol	Listed
	Microbiocide	Listed

IARC:	Titanium Dioxide	Group 2B – Possible carcinogen to humans
	Quartz	Group 1 – Known carcinogen to humans
	Ethylene glycol	Group 2A – Probable carcinogen to humans

#### SARA Title III



# SAFETY DATA SHEET

## EXCEL FLAT EMULSION



Section 311/312:	Propylene glycol	Immediate (Acute) Health and Delayed (Chronic) Health Hazard
	Ethylene glycol	Immediate (Acute) Health and Delayed (Chronic) Health Hazard
	Titanium dioxide	Immediate (Acute) Health and Delayed (Chronic) Health Hazards
	Triton X-100	Immediate (Acute) Health Hazard Immediate (Acute) Health Hazard
WHMIS:	Titanium Dioxide	Class D, Div 2 Sub Div A: Material causing other toxic effects (VERY TOXIC)
	Quartz	Class D, Div 2 Sub Div A: Material causing other toxic effects (VERY TOXIC)
	Propylene glycol	Class D, Div 2 Sub Div B: Material causing other toxic effects (TOXIC)
DSL:	Titanium Dioxide	Listed
	Propylene glycol	Listed
	Ethylene glycol	Listed
	Talc	Listed
	Quartz	Listed
TSCA:	Titanium Dioxide	Listed
	Propylene glycol	Listed
	Ethylene glycol	Listed
	Talc	Listed
	Quartz	Listed

### SECTION 16: OTHER INFORMATION

The information contained herein is based on data available at the time of preparation of this data sheet and which is believed to be reliable. However, it is the users' responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This information is given in good faith, but no warranty, expressed or implied is made.