

# TECHNICAL DATA SHEET

## TROWELTEX

### BRUSHING SOLUTION



#### DESCRIPTION



**Troweltex Brushing Solution** is a styrene acylic based flat emulsion paint, specially formulated for use over Harris Troweltex and other textured finishes. Its principal features, which make it ideal for this purpose, include low viscosity, high hiding power and excellent fungus resistance.

#### COLOUR RANGE

Coral 048

#### COVERAGE

Up to 400 sq. ft. per U.S. gallon (10 sq. m./litre) depending on surface texture.

**Number of Coats:** 1 to 2 coats.

#### DIRECTIONS FOR USE

Troweltex Brushing Solution may be applied by brush. Stir well before use.

The product is supplied ready to use from the can but if thinning is necessary use a small quantity (no more than ½ pint per gallon) of clean water. Prepare all surfaces by removing dirt, dust, grease and mildew. Areas affected by mildew should be washed with a solution of 125ml liquid bleach and 15ml non-ammoniated liquid detergent per litre of water, before the application of Troweltex Brushing solution.

#### DRYING TIME

Touch dry in 1-2 hours.

Recoat After 2-4 hours – dependent upon conditions

Curing Time: 7 days dependent upon conditions

#### CLEAN- UP

Clean water. Tools and equipment should be cleaned with water immediately after use.

# TECHNICAL DATA SHEET

## TROWELTEX

### BRUSHING SOLUTION



#### COMPOSITION

Titanium dioxide selected inert pigments, calcium carbonate, mica, clay, talc, organic biocides, surfactants and specialty additives in a vehicle of acrylic or copolymer latex.

#### PRODUCT CHARACTERISTICS

<b>Thinner</b>	Water
<b>Pot Life</b>	Not applicable. Single component.
<b>Storage Life</b>	2 years minimum

#### PACKAGING SIZES

Available in 1 US gallon, 2 gallon and 5-gallon sizes.

#### PRECAUTIONS

**KEEP OUT OF REACH OF CHILDREN**

**SAFETY DIRECTIONS**

**NON-FLAMMABLE.** Store in a cool place. Non-toxic under normal conditions.

**FIRST AID:** In case of skin contact, wash thoroughly with soap and water. If product comes into contact with eyes, flush immediately with plenty water and seek medical advice. **DO NOT SWALLOW.** If ingested seek medical advice immediately.

#### TECHNICAL ASSISTANCE

For advice and recommendation on the use of all Harris/BH Paints and Building Products, consult the Harris Technical Department, Tel: (246) 429-4840.

Email: [technical@harrispaintsonline.com](mailto:technical@harrispaintsonline.com)