

# TECHNICAL DATA SHEET

## TROWELTEX TEXTURED FINISH



### DESCRIPTION



**TrowelTex** is a textured coating based on waterborne styrene acrylic copolymer, ideal for transforming interior and exterior surfaces with stone-like finish.

Available in 4 grades – Superfine, Fine, Medium and Coarse.

### COLOUR RANGE

Natural; Can also be tinted in a wide range of colours.

### FEATURES

- Excellent coverage
- Interior or exterior usage
- Provides an even finish over minor surface imperfections
- Easy to apply using trowel or spray gun (should be applied by a professional)
- Mildew and water resistant
- Can be custom tinted

### SPREAD RATE

- Superfine – 1.2kg/m<sup>2</sup> (2.5 lb per square yard)\*
- Fine – 1.6kg/m<sup>2</sup> (3.5 lb per square yard)
- Medium – 2.0kg/m<sup>2</sup> (4.5 lb per square yard)
- Coarse - 2.4kg/m<sup>2</sup> (5.5 lb per square yard)

#### Number of Coats: 1

\*Under some conditions, 2 coats of Superfine may be required for best results.

### DIRECTIONS FOR USE

TrowelTex Textured Finish may be applied by experienced personnel using trowels or specialised spraying equipment. TrowelTex Textured Finish will adhere to sound, dust-free and mildew-free blockwork, plaster, hardboard or wood and cement boards.

On wood and porous substrates, use of an appropriate primer is recommended. On concrete and cement substrates, TrowelTex Textured Finish may be applied directly to the bare surface, but the finish, appearance and durability may be enhanced by the

# TECHNICAL DATA SHEET

## TROWELTEX TEXTURED FINISH



application of an appropriate primer or basecoat. Troweltex Textured Finish is supplied in a consistency ready for use and should need no thinning. Mix thoroughly before use and thin sparingly with water only if necessary, to ease application.

Below is recommendation for spray application:

<b>Material</b>	<b>Nozzle Size</b>	<b>Sprayers</b>
Troweltex Coarse	6 mm or 8 mm nozzle	Graco RTX1500 or HTX 2030 or equivalent equipment
Troweltex Medium	6 mm or 8 mm nozzle	Graco RTX 1500 or HTX 2030 or equivalent equipment
Troweltex Fine	6 mm nozzle	Graco RTX 1500 or HTX 2030 or equivalent equipment
Troweltex Superfine	6 mm nozzle	Graco RTX 1500 or HTX 2030 or equivalent equipment

### STORAGE LIFE

Minimum 18 months. Best to use as soon as possible after purchase. We recommend that Troweltex Textured Finish should be stored in a cool place away from direct sunlight.

### DRYING TIME

Touch dry: 1 hour depending on atmospheric conditions

Recoat: N/A

Curing time: 1-2 days, dependent upon conditions

### CLEAN- UP

Clean tools and equipment with water immediately after use.

### COMPOSITION

Titanium dioxide, calcium carbonate, calcined clay, mica, organic biocides, styrene acrylic copolymer, cellulose fibres.

### PRODUCT CHARACTERISTICS

<b>Colour &amp; Form</b>	Cream coloured paste; Custom colours.
<b>Solids Content (by weight)</b>	70-78%
<b>Weight per gallon (US)</b>	Approx. 15 lbs (6.8kg)
<b>Gloss at 60°</b>	Matte

# TECHNICAL DATA SHEET TROWELTEX TEXTURED FINISH



## Drying Time

Touch dry in an hour but may be extended depending upon coating thickness and atmospheric conditions

## Thinner

Water

## Pot Life

Not applicable. Single component.

## PACKAGING SIZES

Available in 65lb pail.

## PRECAUTIONS

**KEEP OUT OF REACH OF CHILDREN**

**SAFETY DIRECTIONS**

**NON-FLAMMABLE.** Store in a cool place. Non- toxic under normal conditions.

**FIRST AID:** In case of skin contact, wash thoroughly with soap and water. If product comes into contact with eyes, flush immediately with plenty water and seek medical advice. **DO NOT SWALLOW.** If ingested seek medical advice immediately.

## TECHNICAL ASSISTANCE

For advice and recommendation on the use of all Harris/BH Paints and Building Products, consult the Harris Technical Department, Tel: (246) 429-4840.

Email: [technical@harrispaintsonline.com](mailto:technical@harrispaintsonline.com)