

TECHNICAL DATA SHEET

ULTIMA NON-DRIP

CEILING WHITE



DESCRIPTION



Ultima Non-Drip Ceiling White is a high opacity, copolymer, emulsion paint. It is designed for easy drip-free application by brush or roller, to hardboard, tentest, plywood or concrete ceilings.

Ultima Non-Drip Ceiling White spreads on evenly, and dries to a flat, fresh looking finish, and is resistant to fungus and mildew growth.

COLOUR RANGE

White

FEATURES

- Interior use
- Ideal for most ceilings
- Brilliant white flat finish

SPREAD RATE

- **RECOMMENDED MAXIMUM WET FILM THICKNESS PER COAT:**
200 microns (8 mils)
- **RECOMMENDED MAXIMUM SPREAD RATE PER COAT:**
7.5-8.8 m² per litre (300-350 sq. ft/ US gal)

DIRECTIONS FOR USE

Ultima Non-Drip Ceiling White may be applied by brush or roller to clean dust-free surfaces. For recoating, one coat is usually sufficient. However, to ensure an even consistency and to make the paint become more fluid for application, an initial light stirring may be employed. Thinning is not needed and should be avoided. Nail heads should be countersunk, filled and sanded before painting.

TECHNICAL DATA SHEET

ULTIMA NON-DRIP

CEILING WHITE



RECOMMENDED PAINT SYSTEMS

<i>For Concrete, Drywall, Teneat, Hardboard Surfaces</i>	<i>For Wooden Surfaces</i>
<ul style="list-style-type: none"> • Prime with one (1) coat of Harris/BH Ultima Concrete & Drywall Primer • 1-2 coats of Harris/BH Ultima Non-Drip Ceiling White 	<ul style="list-style-type: none"> • Prime with one (1) coat of Harris/BH Ultima Wood Primer or Super Grip Premium Problem-Solving Primer • 1-2 coats of Harris/BH Ultima Non-Drip Ceiling White

GENERAL SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds and loose and flaking paint.

NEW SURFACES

Concrete and Masonry: Allow curing for at least 30 days before painting. Remove any loose aggregate from the surface and roughen the surface of slick, smooth concrete by acid etching. Ensure to carefully follow the manufacturer's application and safety instructions. Rinse thoroughly with water and allow to dry. Prime with Ultima Concrete & Drywall Primer.

Wood: Spot prime knots with a knotting sealer. Sand the surface smooth and wipe clean. Prime surface with Ultima Wood Primer or Super Grip Premium Problem-Solving Primer.

PREVIOUSLY PAINTED SURFACES

Harris/BH Super Seal Premium Bonding Primer/Sealer is ideal for sealing old, dusty, chalky surfaces before top coating with an emulsion paint. Remove heavily chalked or dusty areas with detergent and water and allow to air dry. Then treat surfaces with Super Seal Premium Bonding Primer/Sealer and allow to dry before applying Non-Drip Ceiling White.

For previously painted oil surfaces, sand lightly and/or apply Harris/BH Super Grip Premium Problem-Solving Primer and then apply a coat of Ultima Non-Drip Ceiling White.

DRYING TIME

Touch dry: Approx. 20 minutes

Recoat: After 2 hours

Curing time: 7 days

TECHNICAL DATA SHEET

ULTIMA NON-DRIP

CEILING WHITE



CLEAN- UP

Clean tools and equipment with warm soapy water immediately after use.

COMPOSITION

Resin Type	Acrylic Latex
Pigments	Titanium dioxide, selected inert pigments, calcium carbonate, mica, clay, talc
Solvents	Water
Biocides	Organic biocides
Additives	Surfactants, Specialty additives

PROPERTIES

Colour	White
Thinner	Water
Dry to Touch (6 mils.)	20 mins at 25°C
Recoat	After 2 hours
Gloss at 60°	Matte; Less than 3
Volatile organic content (VOC)	14 grams per litre
Viscosity (Kreb Units)	116 K.U
Solids by weight	48%
Weight per gallon (US)	11.0 lbs/gallon
PH	9.0
Shelf Life	2 years minimum-unopened

PACKAGING SIZES

Available in 3.8 litres (1 US gal) and 19 litres (5 US gal).

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

SAFETY DIRECTIONS

NON- FLAMMABLE. Store in a cool place. Non- toxic under normal conditions.

FIRST AID: In case of skin contact, wash immediately with water. If product comes into contact with eyes, rinse immediately with plenty of water and seek medical advice. **DO NOT SWALLOW.** If ingested, give plenty of water and obtain medical advice.

TECHNICAL DATA SHEET ULTIMA NON-DRIP CEILING WHITE



TECHNICAL ASSISTANCE

For advice and recommendation on the use of all Harris/BH Paints and Building Products, consult the Harris Technical Department, Tel: (246) 429-4840.
Email: technical@harrispaintsonline.com