

SAFETY DATA SHEET

MORTAR BOND PVA



SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Supplier:	Harris Group of Companies Willey, St. Michael Barbados, BB14006 Tel: 246-429-4840		
Product Code and Name:	14/1021 Mortar Bond PVA		
Manufacturer:	Harris Group of Companies Willey, St. Michael, Barbados, BB14006		
General Information:	Technical Department Harris Paints Barbados (2003) Limited	Tel: (246) 429-4840 Fax: (246) 436-9544	E-Mail: technical@harrispaintsonline.com
Product Use:	Masonry Bonding Agent – Building Agent		
Date of Preparation:	February 15, 2021	Revision#: 2	

SECTION 2: HAZARDOUS COMPOSITION OF INGREDIENTS AND INFORMATION

INGREDIENTS NAMES			COMPOSITION % (Wt/Gal.)
Common Name	Chemical Name	CAS No.	G-8130
Ammonia	Ammonia	7664-41-7	0.03
Sodium Benzoate	Sodium Benzoate	532-32-1	0.82
Acetaldehyde, Acetic Aldehyde, Ethyl Aldehyde	Acetaldehyde	75-07-0	0.02
Formaldehyde, Formalin	Formaldehyde	50-00-0	0.04
Vinyl Acetate	Vinyl Acetate	108-05-4	0.11

SECTION 3: HAZARDS IDENTIFICATION

Physical State and Appearance	Liquid (viscous)
Primary Routes of Exposure	Skin contact, Inhalation, Eye contact, Ingestion
Possible Effects to Overexposure	Skin contact:- Irritation of skin. May aggravate pre-existing skin conditions.

SAFETY DATA SHEET

MORTAR BOND PVA



<p>Inhalation :- Irritation of respiratory tract. Prolonged inhalation may lead to mucous membrane irritation, dizziness and/or light-headedness, headache, nausea, asphyxiation.</p> <p>Eye contact :- Irritation of eyes. Prolonged or repeated contact may cause conjunctivitis.</p> <p>Ingestion :- Ingestion may cause mouth and throat irritation, gastro-intestinal disturbances.</p> <p>Medical condition aggravated by exposure: Eye, skin, respiratory disorders, kidney disorders, central nervous system depression.</p>
--

SECTION 4: FIRST-AID MEASURES	
Skin Contact:	Flush skin with water. Then wash thoroughly with soap and water. Remove contaminated clothing. Wash contaminated clothing before re-use.
Inhalation:	Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation caused eye watering, headaches, dizziness or other discomfort.
Eye Contact:	Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.
Ingestion:	Flush out mouth. If swallowed, do not induce vomiting. If victim is conscious give at least 2 glasses of water. Obtain medical treatment immediately.

SECTION 5: FIRE-FIGHTING MEASURES	
Flammability of the product:	Lower Explosive Limit: Not Known Upper Explosive Limit: Not Known
Auto-Ignition Temperature:	Not known
Flash Points:	Not known
Fire Extinguishing Media:	Use dry chemical, water foam or fog, carbon dioxide
Products of Combustion:	Carbon dioxide, carbon monoxide, other irritating gases
Unusual Fire and Explosion Hazards:	Ingredients Acetaldehyde and Vinyl Acetate are flammable and fire and/or explosion risks. Also contains very flammable and toxic ingredient Formaldehyde which emits toxic fumes under fire conditions. Be careful of vapours in container heads.

SAFETY DATA SHEET

MORTAR BOND PVA



SECTION 6: ACCIDENTAL RELEASE MEASURES	
Small Spill and Leak:	Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Spills may be collected with absorbent materials. Place collected material in an appropriate container. Complete personal protective equipment must be used during clean-up.
Large Spills and Leaks:	Shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessel. Use absorbent to collect excess residue.

SECTION 7: HANDLING AND STORAGE	
Handling:	Store cool at a constant temperature. Keep away from heat, sparks and open flames. Minimum: 1°C Maximum: 40°C.
Storage:	Polypropylene pails
Other Precautions:	Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes and breathing of vapours. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or sanding painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under Exposure Control/Personal Protection. Empty containers may contain residues.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION			
Common Name	CAS No.	ACGIH-TLV 8-Hour TWA	OSHA-PEL 8-Hour TWA
Ammonia	7664-41-7	25 ppm	25 ppm
Sodium Benzoate	532-32-1	Not available	Not available
Acetaldehyde, Acetic Aldehyde, Ethyl Aldehyde	75-07-0	Not available	100 ppm
Formaldehyde, Formalin	50-00-0	0.3 ppm	0.75 ppm
Vinyl Acetate	108-05-4	10 ppm	10 ppm
Body	Impervious clothing should be worn to eliminate possible skin irritation		
Hands	Impervious gloves such as neoprene or nitrile rubber gloves should be worn.		
Respiratory	Use in a well-ventilated area or provide local exhaust or ventilation to reduce vapours build up. Use of an appropriate NIOSH/MSHA approved or equivalent electrometric sealing surface face piece respirator outfitted with organic vapour cartridges and paint spray (Dust/Mist) prefilters.		
Eyes	Safety goggles or glasses recommended especially for overhead work. Face shield could be used to protect facial skin also.		

SAFETY DATA SHEET

MORTAR BOND PVA



N.B.: Keep running water sources on site in cases of emergency and for after work cleaning.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance:	Liquid	Odour:	Slight
pH:	5.3 – 6.3	Colour:	White
Soluble/Insoluble:	Soluble in water	Viscosity:	88 KU
Melting/Freezing Point:	Not available	Solubility:	Not available
Boiling/Condensation Point:	Not available	Critical Temperatures:	Not available
Specific Gravity:	1 – 1.04	Volatility:	Not available
Vapour Density:	Not available	Vapour Pressure:	Not available
Evaporation Rate:	Not available		

SECTION 10: STABILITY AND REACTIVITY

Stability and reactivity: This product is stable. See Section 5 Fire Fighting Measures.

Conditions to avoid: Elevated temperatures, contact with oxidising agents, sparks, freezing, open flame.

Materials to avoid: Oxidisers, acids.

SECTION 11: TOXICOLOGICAL INFORMATION

Supplemental Health Information: No additional effects are anticipated besides those mentioned in Section 5 Fire Fighting Measures.

This product has not been listed by IARC, OSHA, ACGIH, DSL, TSCA but contains ingredients which are toxic by ingestion, inhalation and through the skin.

Carcinogenicity IARC has classified formaldehyde and vinyl acetate as a possible carcinogen to humans based on sufficient evidence in animals and inadequate evidence in humans.

SECTION 12: ECOLOGICAL INFORMATION

There is no data available on the product.

General Note: Do not allow undiluted product or large quantities of product to reach ground water, water courses or sewage systems.

SECTION 13: DISPOSAL CONSIDERATION

Dispose of in accordance with all applicable regulations ensuring no contamination of surrounding environment.

SECTION 14: TRANSPORTATION INFORMATION

UN ID No.:

This product is not controlled or regulated under DOT, IATA.

SAFETY DATA SHEET

MORTAR BOND PVA



SECTION 15: REGULATORY INFORMATION

Products

As of the date of this MSDS, this product was not being regulated or controlled.

Product Components:

EINECS No.: Titanium Dioxide – 236-675-5, Sodium Benzoate – 208-534-8,
Formaldehyde – 231-867-5

DSCL (EEC) Ammonia
IARC Titanium dioxide
Vinyl Acetate
Formaldehyde

SARA Title III

Section 311/312: Ammonia - Immediate (Acute) and Delayed (Chronic) Health Hazard, Fire, Sudden Release of Pressure and Reactive Hazards

Section 313: Ammonia
Vinyl Acetate

WHMIS: Acetaldehyde

DSL: Titanium Dioxide - Listed
Acetaldehyde - Listed
Vinyl Acetate - Listed

TSCA: Ammonia - Listed
Sodium Benzoate - Listed

ATSDR: Ammonia

SECTION 16: OTHER INFORMATION

The information contained herein is based on data available at the time of preparation of this data sheet and which is believed to be reliable. However, it is the users' responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This information is given in good faith, but no warranty, expressed or implied is made.

This SDS complies with SDS requirements for Canada, the USA and the European Union and fulfils the ISO standards for format and content.