



SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Supplier: Harris Group of Companies

Wildey, St. Michael Barbados, BB14006 Tel: 246-429-4840

Product Code and

17/1010 and 17/2036 Ulttima Puritene Oil Paint Thinner

Name:

17/1013 and 17/2037 Ulttima Lacquer Thinner

17/2035 Ulttima Xylol Thinner

Manufacturer: Harris Group of Companies

Wildey, St. Michael, Barbados, BB14006

General Information: Technical Department

Tel: (246) 429-4840 Fax: (246) 436-9544

Harris Paints Barbados (2003) Limited

E-Mail: technical@harrispaintsonline.com

Product Use: Thinner/Solvent

Date of Preparation: February 17, 2022 Revision#: 4

SECTION 2: HAZARDOUS COMPOSITION OF INGREDIENTS AND INFORMATION			
INGREDIENTS NAMES	COMPOSITION % (Wt./Gal.)		

Common Name	Chemical Name	CAS No.	17/1010	17/2035	17/1013
			and		and
			172036		17/2037
Mineral Spirits, Stoddard	Aliphatic Hydrocarbons	8052-41-	97.3		
Solvent		3			
Xylene	Xylene (mixed isomers)	1330-20-	2.7	100	
		7			
Toluene	Methylbenzene,	108-88-3			60.5
	Phenylmethane				
Acetone	2-propanone, Dimethylketone	67-64-1			17.5
Isopropyl alcohol	2-propanol, isopropanol	67-63-0			12.0
Butyl Cellosolve	2-butoxy-ethanol	111-76-2			10.0





SECTION 3: HAZARDS IDENTIFICATION			
Physical State and Appearance: Liquid			
Primary Routes of Exposure: Skin contact, Inhalation, Eye contact, Ingestion			
Possible Effects to Overexposure:			
Skin contact:-	Irritation of skin. May aggravate pre-existing skin conditions.		
Inhalation:- Eye contact:-	Irritation of respiratory tract. Prolonged inhalation may lead to mucous membrane irritation, dizziness and/or light-headedness, headache, nausea, asphyxiation. Irritation of eyes. Prolonged or repeated contact may cause		
Lyc contact.	conjunctivitis.		
Ingestion:-	Ingestion may cause mouth and throat irritation,		
	gastro-intestinal disturbances.		
Medical condition aggravated by exposure: Eye, skin, respiratory disorders, kidney disorders, central			
nervous system depression.			

SECTION 4:	FIRST-AID MEASURES			
Skin Contact:	Skin Contact: Flush skin with water. Then wash thoroughly with soap and water. Remove contaminated clothing. Wash contaminated clothing before re-use.			
Inhalation:	Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation caused eye watering, headaches, dizziness or other discomfort.			
Eye Contact:	Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.			
Ingestion:	Flush out mouth. If swallowed, do not induce vomiting. If victim is conscious give at least 2 glasses of water. Obtain medical treatment immediately.			

SECTION 5: FIRE-FIGHTING MEASURES			
Flammability of the product:	Lower Explosive Limit: Not Available		
	Upper Explosive Limit: Not Available		
Auto-Ignition Temperature:	> 240° C		
Flash Points:	< 65° C		
Fire Extinguishing Media:	Use dry chemical, water foam or fog, carbon dioxide		
Products of Combustion:	Carbon dioxide, carbon monoxide, other irritating gases		
Unusual Fire and Explosion Hazards: Closed containers may burst if exposed to extreme heat or fire			
Special Remarks on Fire Hazards:	These Thinner products contain substances which are dangerous fire risks		
	especially the Lacquer Thinner ¹ .		
Special Remarks on	Lacquer Thinner ¹ has an explosive limits range of 1.2 – 13.0		
Explosion Hazards:			





SECTION 6: ACCIDENTAL RELEASE MEASURES			
Small Spill and Leak: Comply with all applicable health and environmental regulations.			
	Eliminate all sources of ignition. Ventilate area. Spills may be collected with		
	absorbent materials. Place collected material in an appropriate container.		
	Complete personal protective equipment must be used during clean-up.		
Large Spills and Leaks:	Shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage		
	vessel. Use absorbent to collect excess residue.		

SECTION 7: HANDL	ING AND STORAGE
Handling:	Store cool at a constant temperature. Keep away from heat, sparks and open
	flames.
	Minimum: 1°C Maximum: 40°C.
Storage:	Steel tins, plastic bottles.
Other Precautions:	Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes and breathing of vapours. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying. If such conditions cannot be avoided, use appropriate respiratory protection as directed under Exposure Controls/Personal Protection. Empty containers may contain residues.

SECTION 8: EXPO	SURE CONTR	OLS/PEF	RSONAL PROTECTION			
Common Name		CAS No.	ACGHI-TLV	OSHA-PEL		
			8-Hour TWA	8-Hour TWA		
Mineral Spirits, Stoddard Solvent			8052-41-3	100 ppm	500 ppm	
Xylene			1330-20-7	100 ppm	100 ppm	
Toluene	Toluene		108-88-3	50 ppm	100 ppm	
Acetone			67-64-1	500 ppm	1000 ppm	
Isopropyl alcohol			67-63-0	400 ppm	400 ppm	
Butyl Cellosolve			111-76-2	25 ppm	50 ppm	
Personal Protection				1	1	
Body Impervious clothing should be worn to eliminate possible skin irri			sible skin irritation.			
	Hands	Impervious gloves such as neoprene or nitrile rubber gloves should be				
		worn.				
	Respiratory	Use in a well-ventilated area or provide local exhaust or ventilation to				
		reduce vapours build up. Use of an appropriate NIOSH/MSHA approved				
		or equivalent electrometric sealing surface face piece respirator outfitted				
		with organic vapour cartridges and paint spray (Dust/Mist) prefilters.				
		Ensure filters are regularly changed to avoid build-up of vapour in filters				
		with o	rganic vapour cartridge e filters are regularly ch	es and paint spray (Dus	t/Mist) prefilte	





Eyes Safety goggles or glasses recommended especially for overhead work.

Face shield should be used to protect facial skin also.

N.B.: Keep running water sources on site in cases of emergency and for after work cleaning.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES			
Physical State and Appearance: Liquid	Odour: Solvent/Characteristic		
pH: Not available	Colour: Clear		
Soluble/Insoluble: Soluble in water, alcohol	Viscosity: Not available		
Melting/Freezing Point: Not available	Solubility: Not available		
Boiling/Condensation Point: Not available	Critical Temperatures: Not available		
Specific Gravity: 0.74 – 0.96	Volatility: Not available		
Vapour Density: Not available	Vapour Pressure: Not available		
Evaporation Rate: Not available			

SECTION 10: STABILITY AND REACTIVITY

Stability and reactivity: These products are stable. See Section 5 Fire Fighting Measures.

Conditions to avoid: Elevated temperatures, contact with oxidising agents, sparks, freezing, open flame.

Materials to avoid: Oxidisers, acids.

SECTION 11: TOXICOLOGICAL INFORMATION

Supplemental Health

Information: No additional effects are anticipated besides those mentioned in Section 5 Fire Fighting

Measures.

These products have not been listed by IARC, OSHA, ACGIH, DSL, TSCA but contain

ingredients which are toxic by ingestion, inhalation and through the skin.

SECTION 12: ECOLOGICAL INFORMATION

There is no data available on the products.

General Note: Do not allow undiluted product or large quantities of products to reach ground water, water courses or sewage systems.

SECTION 13: DISPOSAL CONSIDERATION

Dispose of in accordance with all applicable regulations ensuring no contamination of surrounding environment.





SECTION 14: TRANSPORTATION INFORMATION

UN ID No.: 1263

These products are not controlled or regulated under DOT, IATA.

DOT: Classification: Paints "protect from freezing" IATA: Classification: Paints "protect from freezing"

SECTION 15: REGULATORY INFORMATION

Products

As of the date of this SDS, these products were not being regulated or controlled.

Product Components:

EINECS No.: Xylene - 215-535-7, DSCL (EEC): Stoddard Solvent

IARC: Xylene

SARA Title III

Section 311/312: Butyl cellosolve - Acute, Chronic, Fire

Acetone - Acute, Fire

Stoddard Solvent - Acute, Chronic, Fire

Isopropyl alcohol - Acute, Fire

Section 313: Toluene

Acetone

Isopropyl alcohol

WHMIS: Isopropyl alcohol

Butyl cellosolve

Acetone

DSL: Acetone - Listed

Xylene - Listed

Stoddard Solvent - Listed

TSCA: Butyl cellusolve - Listed

Acetone - Listed Isopropyl alcohol - Listed

Stoddard Solvent - Listed

ATSDR:

SECTION 16: OTHER INFORMATION

The information contained herein is based on data available at the time of preparation of this data sheet and which is believed to be reliable. However, it is the users' responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This information is given in good faith, but no warranty, expressed or implied is made.

This SDS complies with SDS requirements for Canada, the USA and the European Union and fulfils the ISO standards format and content.