

SAFETY DATA SHEET

DURAGLAZE QUICK DRYING WOODSTAIN



SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Supplier:	Harris Group of Companies Wildey, St. Michael Barbados, BB14006 Tel: 246-429-4840		
Product Code and Name:	19/2084 Duraglaze Quick Drying Woodstain		
Manufacturer:	Harris Group of Companies Wildey, St. Michael, Barbados, BB14006		
General Information:	Technical Department Harris Paints Barbados (2003) Limited	Tel: (246) 429-4840 Fax: (246) 436-9544	E-Mail: technical@harrispaintsonline.com
Product Use:	Coating/Varnish		
Date of Preparation:	February 15, 2021	Revision#: 1	

SECTION 2: HAZARDOUS COMPOSITION OF INGREDIENTS AND INFORMATION

INGREDIENTS NAMES			COMPOSITION % (Wt./Gal.)
Common Name	Chemical Name		F-5000
Propylene Glycol	1,2-Propylene Glycol	57-55-6	1.7
Texanol	Propanoic Acid, 2, 2, 4-Trimethyl-1, 3-Pentanediol Monoisobutyrate	25265-77-4	0.29
Microbiocides Mixture	N/A: Acticides (Mixture)	NA	0.36
Ammonia	Ammonia	7664-41-7	0.03

SECTION 3: HAZARDS IDENTIFICATION

Physical State and Appearance	Liquid (viscous)
Primary Routes of Exposure	Skin contact, Inhalation, Eye contact, Ingestion.

SAFETY DATA SHEET

DURAGLAZE QUICK DRYING WOODSTAIN



Possible Effects to Overexposure

Skin contact:- Irritation of skin. May aggravate pre-existing skin conditions.

Inhalation:- Irritation of respiratory tract. Prolonged inhalation may lead to mucous membrane irritation, dizziness and/or light-headedness, headache, nausea, asphyxiation.

Eye contact:- Irritation of eyes. Prolonged or repeated contact may cause conjunctivitis.

Ingestion:- Ingestion may cause mouth and throat irritation, gastro-intestinal disturbances.

Medical condition aggravated by exposure: Eye, skin, respiratory disorders, kidney disorders, central nervous system depression.

SECTION 4: FIRST-AID MEASURES

Skin Contact: Flush skin with water. Then wash thoroughly with soap and water. Remove contaminated clothing. Wash contaminated clothing before re-use.

Inhalation: Remove to fresh air. Restore and support continued breathing. Get emergency medical attention.

Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation caused eye watering, headaches, dizziness or other discomfort.

Eye Contact: Flush immediately with large amounts of water, especially under lids for at least 15 minutes. Irritation or other effects persist, obtain medical treatment.

Ingestion: Flush out mouth. If swallowed, do not induce vomiting. If victim is conscious give at least 2 glasses of water. Obtain medical treatment immediately.

SECTION 5: FIRE-FIGHTING MEASURES

Flammability of the product: Lower Explosive Limit: Not Known
Upper Explosive Limit: Not Known

Auto-Ignition Temperature: Not known

Flash Points: >100°C

Fire Extinguishing Media: Use dry chemical, water foam or fog, carbon dioxide

Products of Combustion: Carbon dioxide, carbon monoxide, other irritating gases

Unusual Fire and Explosion Hazards: Closed containers may burst if exposed to extreme heat or fire

Explosive Hazard in Presence of Various Substances: As contains ammonia, avoid its contact with silver or mercury.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Small Spill and Leak: Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Spills may be collected with absorbent materials. Place collected material in an appropriate container. Complete personal protective equipment must be used during cleanup.

SAFETY DATA SHEET

DURAGLAZE QUICK DRYING WOODSTAIN



Large Spills and Leaks: Shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessel. Use absorbent to collect excess residue.

SECTION 7: HANDLING AND STORAGE

Handling: Store cool at a constant temperature. Keep away from heat, sparks and open flames
Minimum: 1°C Maximum: 40°C.

Storage: Polypropylene pails or lacquer lined steel tins.

Other Precautions: Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes and breathing of vapours. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or sanding painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under Exposure Controls/Personal Protection. Empty containers may contain residues.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Common Name	CAS No.	ACGHI-TLV 8-Hour TWA	OSHA-PEL 8-Hour TWA
Propylene Glycol	57-55-6	Not est.	Not est.
Texanol	25265-77-4	Not est.	Not est.
Ammonia	7664-41-7	25 ppm	25 ppm
Microbiocides Mixture	NA	Not est.	Not est.

Personal Protection

Body Impervious clothing should be worn to eliminate possible skin irritation
Hands Impervious gloves such as neoprene or nitrile rubber gloves should be worn.
Respiratory Use in a well-ventilated area or provide local exhaust or ventilation to reduce vapours build up.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance:	Liquid	Odour:	Slight
pH:	9	Colour:	Clear / Milky white
Soluble / Insoluble:	Soluble in water	Viscosity:	54 / 55 KU
Melting / Freezing Point:	Not available	Solubility:	Not available
Boiling / Condensation Point:	Not available	Critical Temperatures:	Not available
Specific Gravity:	1.02	Volatility:	Not available
Vapour Density:	Not available	Vapour Pressure:	Not available
Evaporation Rate:	Not available		

SAFETY DATA SHEET

DURAGLAZE QUICK DRYING WOODSTAIN



SECTION 10: STABILITY AND REACTIVITY	
Stability and reactivity:	These products are stable. See Section 5 Fire Fighting Measures.
Conditions to avoid:	Elevated temperatures, contact with oxidising agents, sparks, freezing, open flame.
Materials to avoid:	Oxidisers, acids.

SECTION 11: TOXICOLOGICAL INFORMATION	
Supplemental Health Information:	No additional effects are anticipated besides those mentioned in Section 5 Fire Fighting Measures.
	These products have not been listed by IARC, OSHA, ACGIH, DSL, TSCA but contain ingredients which are toxic by ingestion, inhalation and through the skin.

SECTION 12: ECOLOGICAL INFORMATION	
	There is no data available on the products.
General Note:	Do not allow undiluted product or large quantities of product to reach ground water, water courses or sewage systems.

SECTION 13: DISPOSAL CONSIDERATION	
	Dispose of in accordance with all applicable regulations ensuring no contamination of surrounding environment.

SECTION 14: TRANSPORTATION INFORMATION	
UN ID No.:	These products not controlled or regulated under DOT, IATA.
DOT: Classification:	Paints "protect from freezing"
IATA: Classification:	Paints "protect from freezing"

SAFETY DATA SHEET

DURAGLAZE QUICK DRYING WOODSTAIN



SECTION 15: REGULATORY INFORMATION

Products	As of the date of this SDS, these products were not being regulated or controlled.		
Product Components:	Texanol - 246-771-9,		
EINECS No.:	Microbiocide constituents - Xn – Harmful		
DSCL (EEC):	Trade names Acticide BG and Acticide EPW classified according to 91/155 EC obtained from THOR GmbH.		
IARC:			
SARA Title III			
Section 311/312:	Propylene Glycol	-	Immediate (Acute) Health Hazard
	Ammonia	-	Immediate (Acute); Delayed (Chronic) Health Hazards, Fire Hazard, Sudden Release of Pressure and Reactive Hazards
Section 313:	Ammonia		
WHMIS:			
DSL:	Propylene Glycol	-	Listed
	Ammonia	-	Listed
TSCA:	Propylene Glycol	-	Listed
	Ammonia	-	Listed
ATSDR:	Propylene Glycol	-	Inhalation :- Intermediate 0.009
	ppmAmmonia	-	Inhalation :- Acute 0.5 ppm
			Chronic 0.3 ppm
		Oral :-	0.3 mg/kg/day

SECTION 16: OTHER INFORMATION

The information contained herein is based on data available at the time of preparation of this data sheet and which is believed to be reliable. However, it is the users' responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This information is given in good faith, but no warranty, expressed or implied is made.

This SDS complies with SDS requirements for Canada, the USA and the European Union and fulfils the ISO standards for format and content.