


TECHNICAL DATA SHEET

DURAGLAZE QUICK DRYING WOODSTAIN



DESCRIPTION



Duraglaze Quick Drying Woodstain is a pure acrylic non-yellowing water-based varnish and stain, which is practically odourless, making it ideal for interior use.

Its durable finish resists mildew and fungal growth making it suitable also for exterior application. It requires no under-coats or primers and only moderate sanding of uncoated dry wood before the first coat. In clear it is ideal for glazing un-coated wood or as a topcoat over previously coated finishes in need of additional protection or revival or is available in a variety of rich semi-transparent stain colours.

COLOUR RANGE

Clear but also can be tinted to a variety of rich semi-transparent stain colours.

FEATURES

- Interior/Exterior use
- Touch dry in just 15 minutes; ready to recoat in 2 hours
- Lasts up to 4 years on vertical and 2 years on horizontal exterior surfaces
- Attractive, longer lasting colours
- Low VOC and Low odour making it great for indoors
- Easy to apply, easy water clean-up and easy to maintain

COVERAGE

Largely dependent upon the texture and porosity of the surface to be covered.

DIRECTIONS FOR USE

SURFACE PREPARATION:

- Surfaces should be clean and free of dust, grease and mildew.

APPLICATION:

Duraglaze Quick Drying Woodstain may be applied by brush, roller or airless spray. Stir well before use.

TECHNICAL DATA SHEET

DURAGLAZE QUICK DRYING WOODSTAIN



DRYING TIME

Touch dry in about 15 minutes; can be recoated in 2 hours. Do not apply if rain is expected within 4 hours.

CLEAN- UP

Clean water. Tools and equipment should be cleaned with water immediately after use.

COMPOSITION

Acrylic emulsion in water, biocides and specialty additives.

PACKAGING SIZES

Available in 945ml (1qt), 3.8 litres (1US gal)

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

SAFETY DIRECTIONS

NON-FLAMMABLE. Store in a cool place. Non-toxic under normal conditions.

FIRST AID: In case of skin contact, wash thoroughly with soap and water. If product comes into contact with eyes, flush immediately with plenty water and seek medical advice. **DO NOT SWALLOW.** If ingested seek medical advice immediately.

TECHNICAL ASSISTANCE

For advice and recommendation on the use of all Harris/BH Paints and Building Products, consult the Harris Technical Department, Tel: (246) 429-4840.

Email: technical@harrispaintsonline.com