

TECHNICAL DATA SHEET

GLOSS NITROCELLULOSE LACQUER



DESCRIPTION



Gloss Nitrocellulose Lacquer forms a very hard and glossy finish on wood. It is ideal for interior furniture and cabinetry.

FEATURES

- Can be applied by spray
- Touch dry in 15 minutes
- Hard dry in one hour

COVERAGE

Dependent on the nature of the wood and the required filling and film-build.

DIRECTIONS FOR USE

Conventional spray equipment or airless spray may be used to apply Gloss Nitrocellulose Lacquer. It will require thinning with Ultima Lacquer Thinner (up to 1:1 by volume) to obtain a suitable working viscosity for the equipment being used.

COMPOSITION

A solution of nitrocellulose and alkyd resins in aromatic, ester and ketone solvents.

PRODUCT CHARACTERISTICS

Thinner	Ultima Lacquer Thinner
Pot Life	Not applicable. Single Component
Storage Life	Two years minimum

PACKAGING SIZES

Available in 945ml (1qt), 3.8 litres (1US gal), 19 litres (5 gal) and 54 gal.

TECHNICAL DATA SHEET

GLOSS NITROCELLULOSE LACQUER



PRECAUTIONS

Keep out of reach of children. Highly flammable. Store in a cool place and keep container closed. Flash Point -5°C (23°F). Use with suitable ventilation and avoid inhalation of the vapours. Use of an approved respirator is recommended during application.

If in contact with eyes, rinse immediately with plenty of water and seek medical advice. If in contact with skin, wipe off immediately and clean with plenty of soap and water or use a proprietary skin cleaner. If swallowed do not induce vomiting, wash mouth out with water and get immediate medical attention.

TECHNICAL ASSISTANCE

For advice and recommendation on the use of all Harris/BH Paints and Building Products, consult the Harris Technical Department, Tel: (246) 429-4840.

Email: technical@harrispaintsonline.com