

TECHNICAL DATA SHEET

GLOSS POLYURETHANE



DESCRIPTION



Gloss Polyurethane forms a high-build, clear, glossy finish on wood. For use on all interior wood surfaces, including floors.

COLOUR RANGE

Clear

FEATURES

- Touch dry in just 30 minutes
- Hard dry in 2 hours
- Suitable for high-traffic areas

COVERAGE

Largely dependent upon the texture and porosity of the surface to be covered.

DIRECTIONS FOR USE

SURFACE PREPARATION:

- Surfaces should be clean and free of dust, grease and mildew.

APPLICATION:

Gloss Polyurethane may be applied by brush, roller or airless spray. Stir well before use. Thinning is not required but if desired thin up to 10% with Ultima Puritene Oil Paint Thinner. For new wood or previously stained surfaces, at least three coats will be required to achieve maximum gloss and durability. For best quality finish, allow each coat to dry and de-nib by rubbing lightly with very fine sandpaper between coats.

For previously varnished surfaces, one or two coats will be required. Sand lightly, between coats for best final appearance.

DRYING TIME

Touch dry in about 30 minutes; can be recoated in 2 hours. Do not apply if rain is expected within 4 hours.

TECHNICAL DATA SHEET

GLOSS POLYURETHANE



CLEAN- UP

Clean tools, equipment and spills with Ulttima Puritene Oil Paint Thinner.
For best maintenance, after cleaning with thinner, wash brushes with warm water and detergent.

COMPOSITION

Polyurethane resins, Mineral spirits, aromatic solvents.

PACKAGING SIZES

Available in 945ml (1qt), 3.8 litres (1US gal)

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

SAFETY DIRECTIONS

FLAMMABLE. Best stored in locations not hotter than 26° C

Ensure maximum ventilation during application and drying.

With spray application use of an appropriate respirator is recommended. Dispose of in accordance with local regulations.

FIRST AID: In case of skin contact, wash thoroughly with soap and water. If product comes into contact with eyes, flush immediately with plenty water and seek medical advice. **DO NOT SWALLOW.** If ingested do not induce vomiting, wash mouth out with water and seek immediate medical attention.

If excessive inhalation exposure symptoms are experienced, seek fresh air.

TECHNICAL ASSISTANCE

For advice and recommendation on the use of all Harris/BH Paints and Building Products, consult the Harris Technical Department, Tel: (246) 429-4840.

Email: technical@harrispaintsonline.com