

# Liquid Wax Item no. 2075

# **Properties**

Colorless, liquid and easy to process wax composition with beeswax for indoor applications. Results in a dirt and water-repellent, grip-proof, diffusion-capable finish.. For all unvarnished or previously stained and oiled wood surfaces like furniture, antiques, toys, etc. Do not use for wet areas, in spray-water areas or other high-traffic areas (e.g. bench tops, stairs, etc.).

# Ingredients

Aromatic-free, highly-purified white spirit, micro-wax, bees wax.

# **Processing steps:**

#### 1. Preparation

Substrate must be dry (max. wood moisture content: 12%) clean, and precisionsanded to a smooth finish; clean with BIOFA Thinner 0500 as needed. Heavily used and absorbent wood parts must first be primed and sanded between coats after drying with BIOFA Universal Wood Primer 3755 solvent-free.

#### 2. Application

Thoroughly mix liquid wax, then apply evenly and distribute with brush, rag, or ball rag. After approx. 1 hour of drying time (20°C/50-55 % rel. humidity), polish to a streak-free finish. Repeat procedure as needed.

<u>Important:</u> Be sure to test product before proceeding! Ensure sufficient fresh air circulation when processing and drying!

#### 3. Equipment cleaning

With BIOFA Thinner 0500.

### Consumption/yield per coat

70-80ml/m<sup>2</sup> or 12-14m<sup>2</sup>/l.

#### **Storage**

Keep cool, dry and properly sealed.

#### Container

1 I and 2.5 I metal containers

### Safety instructions

Keep away from children. WHEN IN-GESTED: Immediately call POISON IN-FORMATION CENTER or get medical help. DO NOT induce vomiting. Read label before use. Do not inhale vapor/aerosol. When sprayed, ensure adequate vacuum collection and respiratory protection. Only use in properly ventilated areas. Explosive vapor/air mixtures can be generated when heated or sprayed! Ensure adequate skin protection when processing. The natural ingredients may generate an odor typical for the product!

#### Disposal

Deposit liquid product leftovers at collection point for old paints/old varnishes, and/or dispose in compliance with local statutory regulations. Minor leftovers and soaked processing materials can be disposed in the household waste after drying out.

Only recycle fully emptied and cleaned containers. Not completely emptied and cleaned containers must be treated and disposed like the product!

German Waste Classification Directive [Abfallverzeichnis Verordnung - AVV] waste code iaw. European waste classification: 08 01 11\*

The information and instructions in the technical leaflet are binding. Prior consultation with the application engineering department of BIOFA is required if a deviation from these specifications is necessary. The generally accepted construction engineering practices must be observed. All previous information is null and void after the publication of this leaflet.