

BIOFA NAPLANA Pflegeemulsion (Floor Care Emulsion) Art. No. 2085

Properties

Consists of natural raw materials for basic care and maintenance. Protects varnished, waxed and oiled floors, furniture surfaces, etc. from soiling and mechanical abrasion. Also suitable for smooth leather and other surfaces. Provides a silk gloss finish after a short drying time without polishing. The treated surfaces are reconditioned, moisture-vapour permeable and dirt-repellent. Always use sparingly on smooth stone floors. Even if used for long periods, no unpleasant wax layers difficult to remove build up if used appropriately. Regular maintenance increases the floor's durability considerably. NAPLANA can be polished mechanically after drying.

Ingredients

Water, carnauba wax, fatty acid alcohol ester, lavandin oil, bergamot oil (contains limes).

Application

Wait for at least 4 weeks before cleaning newly treated floors with NACASA Universalreiniger 4010. Then apply NAPLANA 2085 thinly and evenly (3-5 caps = 75-125 ml in 5 l lukewarm water) with a lint-free, soft cloth or floor mop. Future maintenance intervals depend on the type of stress the substrates are exposed to. On smooth leather and other substrates, NAPLANA can also be used in higher concentrations or undiluted.

Attention! Polished surfaces present a slip hazard! Implement preliminary tests and, if necessary, create test surfaces! Always clean substrates thoroughly prior to treatment with NAPLANA and do not use too much NAPLANA, otherwise streaks may form and there is a risk of slip hazard!

Cleaning of tools

Clean with water and, if necessary, soap.

Storage

Cool, above freezing point and sealed airtight.

Container size

1 l / 5 l / 20 l PE or PP- containers.

Safety instructions

Keep out of reach of children. In case of eye contact, thoroughly flush with water immediately.

Disposal

Dispose of large amounts of residue according to locally applicable legal regulations. Small amounts of residue can be emptied into drains. Dispose of emptied and cleaned containers according to locally applicable legal regulations.

GISCODE: GE 10

Waste Incineration Ordinance[AVV]-
Waste Code according to European Waste
Catalogue: 20 01 30

The data and information provided in this technical data sheet are binding. If it is necessary to deviate from these provisions, the Application Technology Department of BIOFA must be consulted in advance. The general rules for structural engineering are to be complied with. With publication of this technical data sheet all previous data sheets regarding this product are no longer valid.