

Instructions

Your Plank shelving system contains:

- **2 upright oak struts with dowel attached that come pre-drilled for attachment to your wall.**
- **3 oak shelves with straight backs and curved fronts.**

Our Plank shelving units are coated with an acrylic urethane matte Scandinavian finish to help protect them and retain their natural look.

We recommend you use a professional installer to install your Plank shelving system.

You will need:

Six 14 gauge bugle head batten screws for the pre-drilled holes in the upright struts (see fig. 1).




fig. 1
14 gauge bugle

For a studwall, your installer will need to attach the upright struts to line up with the internal studs.

Adjust the height of the shelves to your space and specific needs (as a guide we sit our bottom shelf 115cm from the ground)

Once shelves are placed on the dowel, your shelving system is complete.

Arrange your shelf contents with the majority of weight being over the dowel and fixings. Place items with the most weight at the back of the shelf. There is approximately a 225mm overhang of the shelf at either end.

We recommend a weight of no more than 20 kgs per shelf.

Tasmanian Oak is a warm, dense and resilient hardwood. Timber ranges show strong contrasts in timber colour varying from straw to reddish brown, with intermediate shades of cream to pink. The grain can consist of knots & gum veins, which are all inevitable natural characteristics of the timber. This is all considered a feature of Tasmanian oak and is part of its natural beauty. We cannot guarantee products from these ranges to be light, dark or of matching grain. Colours may vary according to light sources and natural characteristics of the timber. Heat and in particular, sunlight, will alter natural colours.

