UPS 90 Pure Battery



World's Smallest Medical Grade UPS Battery – FDA / FAA Compliant

Hospital Transport & Backup



Ambulance Transport

Air Medical Transport





The UPS 90 Pure was designed from the voices of RT's, nurses and biomed. Hospitals and EMS Teams have been struggling with large and heavy UPS batteries. They are hard to mount and transport with. It is very desirable to have a small UPS battery for transport and backup power. Introducing the UPS 90 Pure by Zopec Medical. The weight is only 5 lbs. with size of 11.5" x 6.5" x 2"! It is powerful with 500W AC Output and Pure Sine Wave. Also, no maintenance for 8 - 12 years. It solves the challenges and is a game changer.



Device Compatibility and Run Times

- HFNC (F&P Airvo2): ~90 min at 37°C and 60 LPM (Approved by F&P Healthcare)
- Heaters (F&P MR850, Hamilton H900, Neptune, Vapotherm I): ~70 min at 37°C and 60 LPM
- HFOV (Oscillators): Vyaire 3100A = ~120 min
- Tecotherm NEO: ~4 hours at 33.5 °C
- Blood Gas Analyzers: 2 3 hours
- Air Medical Equip Backup: Airborne Isolette, Nitric Oxide, ventilators, ECMO pumps, monitors, etc.
- Aerogen Nebulizer (AC or USB controller): Can use simultaneously. Does not impact run times.

UPS 90 Pure Battery System







Specifications

| | | UP | S 90 |) Pi | ıre | | | | | |
|-----|-------|-------|------|-------|------|------|-------|------|------|---|
| | HF | 110 | UP | S90 | Pu | re | | | | |
| | | | 5.0 | lbs | | | | | | |
| 1 | 11.5 | " x " | 6.5" | ' x 2 | 2.0" | (in) | | | | |
| | | | Ye | s | | | | | | |
| | L | ine | Inte | erac | tive | e | | | | |
| | Р | ure | Sin | ie V | Vavo | e | | | | |
| | | | 500 | W | | | | | | |
| | | | Ye | es | | | | | | |
| | | | Ye | s | | | | | | |
| | Dig | jital | LE | D D | ispl | ay | | | | ~ |
| | Yes | s (2 | 0%, | 10% | %, 5 | %) | | | | C |
| (lo | ock | ing | loo | ps۱ | with | zip | o tie | es) | | |
| | | | Ye | s | | | | | | |
| te | e (10 | 0% | sile | ent, | no | mo | vin | g pa | rts) | (|
| | | 2 | 2 Ye | ars | | | | | | ~ |
|)V/ | /50- | 60H | lz o | r 22 | 20-2 | 40V | /50 | -60H | z | |
| | | | 25 | 00 | | | | | | |
| | | | Ye | es | | | | | | |
| 3 | 32 - | 115 | ۶°F | (0 - | 46 | °C) | | | | |
| | 7 | ' ho | urs | or | less | ; | | | | |
| | | | | | | | | | | |

Reference Hospitals











UN38.3 PASSED **Safety A** F©CE□ c US COMPLIANT Certifications UL 94 V-0 UL 62133 E62133 IEC 60601-1 IEC 62133 BS EN 62133 Compliant Compliant Enclosure Compliant Compliant

For Sales Inquiries, please contact:

Our Zopec Medical Sales Team at: <u>Sales@zopec.com</u> or 612-208-9793

Zopec Medical LLC., 3140 104th LN NE, Ste 200, Blaine, MN 55449, USA. WWW.ZOPEC.COM. Version 02.01.24